



MPRIS Support for Multimedia Applications

Ashish Madeti



Media Player Remote Interfacing Specification (MPRIS)



IPC and D-Bus



System and Session Buses



D-Bus Internals

- Services
- Objects
- Interfaces
- Methods
- Signals



D-Bus Internals

- **Services**
 - org.kde.kdeconnect
- **Objects**
 - /modules/kdeconnect/devices/
- **Interfaces**
 - org.kde.kdeconnect.device
 - org.kde.kdeconnect.client



Methods and Signals

calling and being called



MPRIS Interfaces

Object Path: /org/mpris/MediaPlayer2

- Root (org.mpris.MediaPlayer2)
- Player (org.mpris.MediaPlayer2.Player)
- TrackList (org.mpris.MediaPlayer2.TrackList)
- Playlists (org.mpris.MediaPlayer2.Playlists)

The media player *must* implement the first two interfaces.



Root Interface

Methods

[Raise](#) () → nothing

[Quit](#) () → nothing

Properties

CanQuit	b	Read only	
Fullscreen	b	Read/Write	(optional)
CanSetFullscreen	b	Read only	(optional)
CanRaise	b	Read only	
HasTrackList	b	Read only	
Identity	s	Read only	
DesktopEntry	s	Read only	(optional)
SupportedUriSchemes	as	Read only	
SupportedMimeTypes	as	Read only	



Player Interface

Methods

Next	()	→ nothing
Previous	()	→ nothing
Pause	()	→ nothing
PlayPause	()	→ nothing
Stop	()	→ nothing
Play	()	→ nothing
Seek	(x: Offset)	→ nothing
SetPosition	(o: TrackId, x: Position)	→ nothing
OpenUri	(s: Uri)	→ nothing

Signals

[Searched](#) (x: Position)



Player Interface

Properties

PlaybackStatus	s (Playback_Status)	Read only	
LoopStatus	s (Loop_Status)	Read/Write	(optional)
Rate	d (Playback_Rate)	Read/Write	
Shuffle	b	Read/Write	(optional)
Metadata	a{sv} (Metadata_Map)	Read only	
Volume	d (Volume)	Read/Write	
Position	x (Time_In_Us)	Read only	
MinimumRate	d (Playback_Rate)	Read only	
MaximumRate	d (Playback_Rate)	Read only	
CanGoNext	b	Read only	
CanGoPrevious	b	Read only	
CanPlay	b	Read only	
CanPause	b	Read only	
CanSeek	b	Read only	
CanControl	b	Read only	



Testing MPRIS

qdbusviewer and mpristester



Thank You