

The `currency` package^{*}

Antoine Lejay

`Antoine.Lejay@univ-lorraine.fr`

October 24, 2018

1 Introduction

This package creates macros for defined currencies which follow the ISO 4217 codes, with various formatting options for both the currency (code, symbols, names, ...) and the numbers (using `siunitx`).

The currency code ISO 4217 specifies the code of the currency as a three-letters code. The first two ones are the code of the country according to ISO 3166. The last one is the name of the currency name.

2 Licence

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

This work has the LPPL maintenance status ‘maintained’.

The Current Maintainer of this work is Antoine Lejay.

3 Documentation and sources

This package is documented in `currency_doc`.

A source of this package is hosted in

<https://github.com/antoinlejay/currency>

4 Implementation

4.1 Dependencies

^{*}This document corresponds to `currency v0.4`, dated 2018/10/22.

```

1 \RequirePackage{siunitx}
2 \RequirePackage{pgfkeys}
3 \RequirePackage{etoolbox}
4 \RequirePackage{xparse}
5 \RequirePackage{expl3}
6 \RequirePackage{textcomp}
7 \RequirePackage{eurosym}

The unit could be printed before or after
8 \newif\ifcurrencynumber
9 \pgfkeys{/currency/.cd,number/.is if=currencynumber, number=true}
10 \newif\ifprintbefore
11 \pgfkeys{/currency/pre/.is if=printbefore}
12 \pgfkeys{/currency/name/.initial=ZZZ}
13 \pgfkeys{/currency/symbol/.initial=\textcurrency}

```

Defines a style currency, which is general and empty. The styles are then called in order - the currency style - currency (initially empty) - the options passed to the command

```

14 \pgfkeys{/currency/currency/.style={}}
15 \newcommand{\CurrencySetup}[1]{%
16     \pgfkeys{/currency/currency/.style={#1}}%
17 }
18 \newcommand{\CurrencySetupAppend}[1]{%
19     \pgfkeys{/currency/currency/.append style={#1}}%
20 }

```

4.2 Names and symbols definitions

The commands `\currencyName`, `\currencyNames`, `\currencyISO` and `\currencySymbol` are used internally every time a currency is called to define the name, the plural, the ISO code and the symbol associated to a currency.

```

21 \pgfkeys{/currency/name/.store in=\currencyName}
22 \pgfkeys{/currency/plural/.store in=\currencyNames}
23 \pgfkeys{/currency/plural/.initial=\currencyName s}
24 \pgfkeys{/currency/iso/.store in=\currencyISO}
25 \pgfkeys{/currency/symbol/.store in=\currencySymbol}

```

4.3 Keys for formatting

Several keys are devoted to insert tokens before or after the unit and the amount, set up the font, ...

```

26 % between the symbol and the num if before
27 \pgfkeys{/currency/pre-between/.initial={~}}
28 % between the symbol and the num if after
29 \pgfkeys{/currency/post-between/.initial={~}}
30 % tokens that are inserted before
31 \pgfkeys{/currency/before/.initial={}}
32 % append to before
33 \pgfkeys{/currency/before+/.code={\pgfkeys{/currency/before/.append={#1}}}}

```

```

34 % prepend to before
35 \pgfkeys{/currency/before</.code={\pgfkeys{/currency/before/.prefix={#1}}}}
36 \pgfkeys{/currency/after/.initial={} % tokens that are inserted after
37 % append to after
38 \pgfkeys{/currency/after+/.code={\pgfkeys{/currency/after/.append={#1}}}}
39 % prepend to after
40 \pgfkeys{/currency/after</.code={\pgfkeys{/currency/after/.prefix={#1}}}}
41 \pgfkeys{/currency/font/.initial={} % for setting up the fonts
42 % append to the font definition
43 \pgfkeys{/currency/font+/.code={\pgfkeys{/currency/font/.append={#1}}}}
44 % the prefix before the name
45 \pgfkeys{/currency/prefix/.initial={}}

```

Several options are given for printing the kind of unit (iso, plural, name, symbol).

```

46 %
47 \pgfkeys{/currency/kind/.is choice}
48 \pgfkeys{/currency/kind/iso/.code=%
49   {\def\currencyunit{\currencyISO}}}
50 \pgfkeys{/currency/kind/plural/.code=%
51   {\def\currencyunit{\currencyNames}\printbeforefalse}}
52 \pgfkeys{/currency/kind/name/.code=%
53   {\def\currencyunit{\currencyName}\printbeforefalse}}
54 \pgfkeys{/currency/kind/symbol/.code=%
55   {\def\currencyunit{\currencySymbol}}}
56 \pgfkeys{/currency/kind=iso}

```

Options are also define for printing the cents (true, false, always).

```

57 \pgfkeys{/currency/cents/.is choice}
58 \pgfkeys{/currency/cents/true/.code=%
59   {\sisetup{zero-decimal-to-integer=true}}}
60 \pgfkeys{/currency/cents/false/.code=%
61   {\sisetup{zero-decimal-to-integer=true,round-precision=0}}}
62 \pgfkeys{/currency/cents/always/.code=%
63   {\sisetup{zero-decimal-to-integer=false,round-integer-to-decimal=true}}}
64 \pgfkeys{/currency/cents=true}

```

4.4 Dealing with unknown keys

The unknown keys are passed to the `\num` command of `siunitx`, which use the L^AT_EX3 syntax and not the pgf one.

```

65 \ExplSyntaxOn
66 \pgfkeys{/currency/.unknown/.code=%
67 \edef\Unknown{\pgfkeyscurrentname=\pgfkeyscurrentvalue}%
68 \keys_set:nV {siunitx} {\Unknown}%
69   }}%
70 \ExplSyntaxOff

```

4.5 Setting the precision

The key `base` is used to set the precision. Its value is passed to the key `round-precision` of `siunitx`.

```
71 \ExplSyntaxOn
72 \pgfkeys{/currency/base/.code={%
73 \edef\SetPrecision{round-precision=\pgfkeyscurrentvalue}%
74 \keys_set:nV {siunitx} {\SetPrecision}%
75 } }%
76 \ExplSyntaxOff
```

4.6 Defining new currencies

The first argument is the name of the currency, normally its ISO symbol (3 letters). This command defines two global commands.

`\displayCurrency` This is a generic macro for displaying the currency symbol and amount. This macro does not aim at being called directly.

```
77 \ExplSyntaxOn
78 \DeclareDocumentCommand{\displayCurrency}{m o m}{%
79 \begingroup%
80 % default parameters, to put outside
81 \sisetup{round-mode=places,round-precision=2}
82 \IfNoValueTF{#2}{%
83   {\pgfkeys{/currency/.cd,#1,currency}}%
84   {\pgfkeys{/currency/.cd,#1,currency,#2}}%
85 \ifbooleq{currencynumber}{%
86   {\sisetup{parse-numbers=true}}%
87   {\sisetup{parse-numbers=false}}%
88 \edef\value{#3}{% store the value of the currency
89 }%
90 \ifprintbefore{%
91 % true clause / print the unit before
92 \pgfkeys{/currency/font}%
93 \pgfkeys{/currency/before}%
94 \text{\pgfkeys{/currency/prefix}\currencyunit}%
95 \pgfkeys{/currency/pre-between}%
96 \num{\value}\pgfkeys{/currency/after}%
97 \else% print the unit after
98 \pgfkeys{/currency/font}%
99 \pgfkeys{/currency/before}%
100 \num{\value}%
101 \pgfkeys{/currency/post-between}%
102 \text{\pgfkeys{/currency/prefix}\currencyunit}%
103 \pgfkeys{/currency/after}%
104 \fi%
105 \endgroup%
106 }
```

\displayCurrencySymbol This is a generic macro for displaying the currency symbol. This macro does not aim at being called directly.

```

107 \DeclareDocumentCommand{\displayCurrencySymbol}{m o}{
108   \begingroup%
109   \IfNoValueTF{#2}{%
110     {\pgfkeys{/currency/.cd,#1,currency}}%
111     {\pgfkeys{/currency/.cd,#1,currency,#2}}%
112     \pgfkeys{/currency/font}%
113     \pgfkeys{/currency/before}%
114     \text{\pgfkeys{/currency/prefix}\currencyunit}%
115 \pgfkeys{/currency/after}%
116 \endgroup%
117 }
```

\DefineCurrency Define the parameters for a new currency. The first parameter is a three letters code of type XXX (actually, it should be any suitable word). Global commands \dXXX (for printing currency with an amount) and \cXXX (for printing only the symbols) are then defined, as well as a style under the pgfkey /currency/XXX.

```

118 \newcommand{\DefineCurrency}[2]{%
119   \pgfkeys{/currency/#1/.style={#2}}%
120 % define the currency with digits as \dXXX
121 \csgdef{d#1}{\displayCurrency{#1}}
122 % end of \dXXX definition
123 % define the currency symbol as \cXXX with one optional argument
124 % \global\expandafter\DeclareDocumentCommand\csname c#1\endcsname{o}{%
125 \csgdef{c#1}{\displayCurrencySymbol{#1}}
126 % end of \cXXX definition
127 }%
```

4.7 Predefined styles

Some styles are defined to shorten the typesetting.

```

128 \pgfkeys{/currency/@iso/.style={kind=iso}}
129 \pgfkeys{/currency/@symb/.style={kind=symbol}}
130 \pgfkeys{/currency/@sy/.style={kind=symbol}}
131 \pgfkeys{/currency/@name/.style={kind=name}}
132 \pgfkeys{/currency/@na/.style={kind=name}}
133 \pgfkeys{/currency/@plural/.style={kind=plural}}
134 \pgfkeys{/currency/@pl/.style={kind=plural}}
135 \pgfkeys{/currency/no-parse/.style={number=false}}
```

Change History

v0.1

General: Initial version	1	v0.2	General: Adding vXXX as an alias for dXXX	1
------------------------------------	---	------	---	---

v0.3

General: Dropping spurious space
in the definition of cXXX 1

v0.4

General: Change
DeclareDocumentCommand for
compatibility with TeXLive 2018 1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

B	\endcsname	124	43, 45, 47, 48,
\begingroup	79, 108	\endgroup	105, 116
		\expandafter	124
C	\ExplSyntaxOff	70, 76	58, 60, 62, 64,
\csgdef	121, 125	\ExplSyntaxOn	65, 71, 77
\csname	124	F	66, 72, 83, 84,
\currencyISO	24, 49	\fi	92–96, 98, 99,
\currencyName	21, 23, 53		101–103, 110–
\currencyNames	22, 51		115, 119, 128–135
\CurrencySetup	15	G	
\CurrencySetupAppend	18	\global	124
\currencySymbol	25, 55	I	\pgfkeyscurrentname 67
\currencyunit	49, 51,	\ifbool	85
	53, 55, 94, 102, 114	\ifcurrencynumber	8
\cXXX	123, 126	\IfNoValueTF	82, 109
D	\ifprintbefore	10, 90	\pgfkeyscurrentvalue 67, 73
\DeclareDocumentCommand	78, 107, 124	R	\printbeforefalse 51, 53
\def	49, 51, 53, 55	S	
\DefineCurrency	<u>118</u>	\SetPrecision	73, 74
\displayCurrency	<u>77</u> , 121	\sisetup	59,
\displayCurrencySymbol	<u>107</u> , 125		61, 63, 81, 86, 87
\dXXX	120, 122	T	
E	P	\newif	8, 10
\edef	67, 73, 88	\num	96, 100
\else	97	U	\text 94, 102, 114
			\textcurrency 13
V	\pgfkeys	19, 21–25, 27,	
		29, 31, 33, 35,	
		36, 38, 40, 41,	\value 88, 96, 100