

The L^AT_EX metalogox package

v1.07 — 2025/01/23

© 2019, 2023–2025 Brian Dunn
<https://github.com/bdtc/metalogox>

Automatically adjusts the T_EX logo and related, depending on the font.

Font	Default	metalogox
Latin Modern	L ^A T _E X	L ^A T _E X
Times	L ^A T _E X	L ^A T _E X
Bookman	L ^A T _E X	L ^A T _E X
Erewhon	L ^A T _E X	L ^A T _E X
Libre Caslon	L ^A T _E X	L ^A T _E X
Libertinus	L ^A T _E X	L ^A T _E X
IM Fell English	L ^A T _E X	L ^A T _E X
Coelacanth	L ^A T _E X	L ^A T _E X
Alegreya	L ^A T _E X	L ^A T _E X
Helvetica	L ^A T _E X	L ^A T _E X
Antiqua	L ^A T _E X	L ^A T _E X

Abstract

The metalogox package extends the metalogo package to automatically adjust the appearance of the logos T_EX, L^AT_EX, L^AT_EX₂_ε, X_EL^AT_EX, and LuaL^AT_EX, depending on the font detected or the option given to metalogox.

Most of the serif and sans fonts listed at [The L^AT_EX Font Catalogue](#) are supported.

Contents

1	Introduction	3
2	Using the metalogox package	3
3	Code	5
3.1	Required packages	5
3.2	Package options	5
3.2.1	Common synonyms	15
3.2.2	Similar fonts	16
3.3	Manual adjust selection	17
3.4	Font detection	17
3.5	Option declaration	24
3.6	Default settings	24
3.7	Option trigger	25
3.8	Support for the hologo and hvlogos packages	25
A	Change History	27
B	Index	27

1 Introduction

The rendering of the logos \TeX , \LaTeX , $\text{\LaTeX}2_{\varepsilon}$, \XeLaTeX , \XeTeX , and \LuaLaTeX depends on the font, and in some cases the appearance of these logos may be improved with some minor adjustments of the positions of each of the elements. The `metalogox` package, by ANDREW GILBERT MOSCHOU, allows the user to specify these adjustments, but it is left to the user to determine the values to use. The correct value may depend on the font size, but in most cases predefined settings may be used.

The `metalogox` package assigns these settings for `metalogox`. The default is for `LATIN MODERN` and similar. If the font in use is supported by `metalogox`, settings for that font are automatically assigned, overriding the `LATIN MODERN` default. If the user specifies a package option, its settings override the default and also anything set by font detection.

The \LaTeX packages `hologo` and `hvlogos` are also supported when used with `metalogox`.

2 Using the `metalogox` package

- `metalogox (Pkg)` In most cases, it is sufficient to simply load the `metalogox` package after the fonts have been selected:

```
\usepackage{<font packages>}
\setmainfont{Font Name}                                (if using fontspec)
...etc ...
% \renewcommand{\familydefault}{\sfdefault}           (optional)
...
\usepackage{metalogox}
```

Many fonts are supported by `metalogox`, and if one of these is in use then the appropriate settings are assigned automatically, according to the default text body font: $\text{\LaTeX}2_{\varepsilon}$

- `options` If several font packages are used, or a font is not recognized, it may be necessary to specify a `metalogox` package option, which overrides the font detection:

```
\usepackage [baskerville] {metalogox}
```

`\adjustlogos {<package option>}`

`\adjustlogos` may be used to adjust the logos for an unknown font. The mandatory argument is the same as the package options. This is a local change, and may be adjusted as needed.

```
\Fontskrivan                                         (from the aurical package)
\adjustlogos{default} \LaTeXe
\adjustlogos{baskerville} \LaTeXe
\Fontskrivan                                         (from the aurical package)
\adjustlogos{default} \XeTeXe
\adjustlogos{baskerville} \XeTeXe
\Fontskrivan                                         (from the aurical package)
\adjustlogos{default} \LuaTeXe
\adjustlogos{baskerville} \LuaTeXe
```

\autoadjustlogos \autoadjustlogos may be used to make local changes according to the current font:

```
\textsf{Using \autoadjustlogos\LaTeXe}           Using LATEX 2<
\textsf{Using \textrm{\autoadjustlogos\LaTeXe}} Using LATEX 2<
```

\autoadjustlogos* The starred form, \autoadjustlogos*, is used by metalogox at the beginning of the document to set according to the default text body font.

Notes:

- metalogox option names may be found in the following pages, or in the index.
- metalogox options are always lowercase, even if a related package name may have uppercase letters.
- Many options, such as `times`, are used to cover an entire category of related fonts.
- Other options, such as `baskerville`, may be used for unrelated fonts which just happen to work well with the same logo settings.
- For some fonts, X_{PL}L^AT_EX renders the reversed E in the X_{PL}L^AT_EX logo differently than pdfL^AT_EX and LuaL^AT_EX.
- There are sometimes differences between the `TYPE1` and the `OTF/TTF` fonts.
- PDF display software may not render logos well on the screen at small display sizes. Zoom in to judge the quality of the logos.
- The metalogox parameters were set according to the design preferences of the author of the metalogox package. Some may disagree with the design choices which were made, but the results are probably better than the defaults, and the user may take control using the metalogox package directly.
- Since the same settings are usually shared by many fonts, some logos may not be perfect.
- If a font is not known by metalogox then a warning is issued, and a few common options are recommended.

[Unknown font?](#)

- Please contact the author of metalogox if an unknown font is found, especially if it is a common font, as sometimes the font family names are changed. See the contact link on the title page of this document.

3 Code

3.1 Required packages

```

1 \RequirePackage{metalogo}
2
3 \IfFormatAtLeastTF{2020-10-01}{}{\RequirePackage{xparse}}
4
5 \RequirePackage{etoolbox}
```

3.2 Package options

Each of the following is a macro which is activated by passing the option of the same name to `metalogox`, or by calling `\adjustlogos`.

For example, either of the following sets the default metalogo logo adjustments:

```
\usepackage[default]{metalogox}
— or —
\adjustlogos{default}
```

`default` (*Opt*) The L^AT_EX and metalogo default settings.

```

6 \newcommand*{\MLX@default}{%
7   \setlogokern{Te}{-0.1667em}%
8   \setlogokern{eX}{-0.125em}%
9   \setlogokern{La}{-.36em}%
10  \setlogokern{aT}{-.15em}%
11  \setlogokern{Xe}{-.125em}%
12  \setlogokern{eT}{-.1667em}%
13  \setlogokern{eL}{-.125em}%
14  \setlogodrop{0.5ex}%
15 }
```

`accanthis` (*Opt*)

```

16 \newcommand*{\MLX@accanthis}{%
17   \setlogokern{Te}{-0.07em}%
18   \setlogokern{eX}{-0.05em}%
19   \setlogokern{La}{-.26em}%
20   \setlogokern{aT}{-.07em}%
21   \setlogokern{Xe}{-.06em}%
22   \setlogokern{eT}{-.05em}%
23   \setlogokern{eL}{-.06em}%
24   \setlogodrop{0.25ex}%
25 }
```

`alegreya` (*Opt*)

```

26 \newcommand*{\MLX@alegreya}{%
27   \setlogokern{Te}{-0.14em}%
```

```

28     \setlogokern{eX}{-.12em}%
29     \setlogokern{La}{-.23em}%
30     \setlogokern{aT}{-.07em}%
31     \setlogokern{Xe}{-.06em}%
32     \setlogokern{eT}{-.10em}%
33     \setlogokern{eL}{-.12em}%
34     \setlogodrop{0.36ex}%
35 }

```

`algolrevived` (*Opt*)

```

36 \newcommand*{\MLX@algolrevived}{%
37     \setlogokern{Te}{-.17em}%
38     \setlogokern{eX}{-.17em}%
39     \setlogokern{La}{-.40em}%
40     \setlogokern{aT}{-.06em}%
41     \setlogokern{Xe}{-.18em}%
42     \setlogokern{eT}{-.18em}%
43     \setlogokern{eL}{-.12em}%
44     \setlogodrop{0.28ex}%
45 }

```

`antpolt` (*Opt*)

```

46 \newcommand*{\MLX@antpolt}{%
47     \setlogokern{Te}{-.09em}%
48     \setlogokern{eX}{-.08em}%
49     \setlogokern{La}{-.33em}%
50     \setlogokern{aT}{-.07em}%
51     \setlogokern{Xe}{-.07em}%
52     \setlogokern{eT}{-.10em}%
53     \setlogokern{eL}{-.06em}%
54     \setlogodrop{0.36ex}%
55 }

```

`avantgarde` (*Opt*)

```

56 \newcommand*{\MLX@avantgarde}{%
57     \setlogokern{Te}{-.10em}%
58     \setlogokern{eX}{-.04em}%
59     \setlogokern{La}{-.26em}%
60     \setlogokern{aT}{-.10em}%
61     \setlogokern{Xe}{-.04em}%
62     \setlogokern{eT}{-.10em}%
63     \setlogokern{eL}{-.02em}%
64     \setlogodrop{0.40ex}%
65 }

```

`baskerville` (*Opt*)

```

66 \newcommand*{\MLX@baskerville}{%
67     \setlogokern{Te}{-.07em}%
68     \setlogokern{eX}{-.05em}%

```

```

69      \setlogokern{La}{-.26em}%
70      \setlogokern{aT}{-.07em}%
71      \setlogokern{Xe}{-.06em}%
72      \setlogokern{eT}{-.07em}%
73      \setlogokern{eL}{-.06em}%
74      \setlogodrop{0.36ex}%
75 }

```

berenis (*Opt*)

```

76 \newcommand*{\MLX@berenis}{%
77     \setlogokern{Te}{-0.07em}%
78     \setlogokern{eX}{-0.05em}%
79     \setlogokern{La}{-.23em}%
80     \setlogokern{aT}{-.07em}%
81     \setlogokern{Xe}{-.06em}%
82     \setlogokern{eT}{-.10em}%
83     \setlogokern{eL}{-.02em}%
84     \setlogodrop{0.58ex}%
85 }

```

bodoni (*Opt*) Also see **librebodoni**.

```

86 \newcommand*{\MLX@bodoni}{%
87     \setlogokern{Te}{-0.11em}%
88     \setlogokern{eX}{-0.05em}%
89     \setlogokern{La}{-.26em}%
90     \setlogokern{aT}{-.07em}%
91     \setlogokern{Xe}{-.06em}%
92     \setlogokern{eT}{-.10em}%
93     \setlogokern{eL}{-.10em}%
94     \setlogodrop{0.37ex}%
95 }

```

boisik (*Opt*)

```

96 \newcommand*{\MLX@boisik}{%
97     \setlogokern{Te}{-0.09em}%
98     \setlogokern{eX}{-0.07em}%
99     \setlogokern{La}{-.35em}%
100    \setlogokern{aT}{-.07em}%
101    \setlogokern{Xe}{-.07em}%
102    \setlogokern{eT}{-.10em}%
103    \setlogokern{eL}{-.06em}%
104    \setlogodrop{0.55ex}%
105 }

```

bookman (*Opt*)

```

106 \newcommand*{\MLX@bookman}{%
107     \setlogokern{Te}{-0.03em}%
108     \setlogokern{eX}{-0.035em}%
109     \setlogokern{La}{-.25em}%

```

```

110      \setlogokern{aT}{-.00em}%
111      \setlogokern{Xe}{-.030em}%
112      \setlogokern{eT}{-.02em}%
113      \setlogokern{eL}{-.06em}%
114      \setlogodrop{0.36ex}%
115 }

```

charter (*Opt*)

```

116 \newcommand*{\MLX@charter}{%
117     \setlogokern{Te}{-.10em}%
118     \setlogokern{eX}{-.07em}%
119     \setlogokern{La}{-.24em}%
120     \setlogokern{aT}{-.06em}%
121     \setlogokern{Xe}{-.07em}%
122     \setlogokern{eT}{-.10em}%
123     \setlogokern{eL}{-.06em}%
124     \setlogodrop{0.28ex}%
125 }

```

crimson (*Opt*)

```

126 \newcommand*{\MLX@crimson}{%
127     \setlogokern{Te}{-0.05em}%
128     \setlogokern{eX}{-0.05em}%
129     \setlogokern{La}{-.23em}%
130     \setlogokern{aT}{-.07em}%
131     \setlogokern{Xe}{-.06em}%
132     \setlogokern{eT}{-.05em}%
133     \setlogokern{eL}{-.06em}%
134     \setlogodrop{0.36ex}%
135 }

```

coelacanth (*Opt*)

```

136 \newcommand*{\MLX@coelacanth}{%
137     \setlogokern{Te}{-0.09em}%
138     \setlogokern{eX}{-0.05em}%
139     \setlogokern{La}{-.26em}%
140     \setlogokern{aT}{-.07em}%
141     \setlogokern{Xe}{-.06em}%
142     \setlogokern{eT}{-.10em}%
143     \setlogokern{eL}{-.06em}%
144     \setlogodrop{0.32ex}%
145 }

```

didot (*Opt*)

```

146 \newcommand*{\MLX@didot}{%
147     \setlogokern{Te}{-0.11em}%
148     \setlogokern{eX}{-0.09em}%
149     \setlogokern{La}{-.34em}%
150     \setlogokern{aT}{-.11em}%

```

```

151      \setlogokern{Xe}{-.06em}%
152      \setlogokern{eT}{-.12em}%
153      \setlogokern{eL}{-.09em}%
154      \setlogodrop{0.44ex}%
155 }

```

droidserif (*Opt*)

```

156 \newcommand*{\MLX@droidserif}{%
157     \setlogokern{Te}{-0.11em}%
158     \setlogokern{eX}{-0.10em}%
159     \setlogokern{La}{-.30em}%
160     \setlogokern{aT}{-.08em}%
161     \setlogokern{Xe}{-.07em}%
162     \setlogokern{eT}{-.10em}%
163     \setlogokern{eL}{-.08em}%
164     \setlogodrop{0.30ex}%
165 }

```

droidsans (*Opt*)

```

166 \newcommand*{\MLX@droidsans}{%
167     \setlogokern{Te}{-0.11em}%
168     \setlogokern{eX}{-0.10em}%
169     \setlogokern{La}{-.24em}%
170     \setlogokern{aT}{-.08em}%
171     \setlogokern{Xe}{-.07em}%
172     \setlogokern{eT}{-.10em}%
173     \setlogokern{eL}{-.08em}%
174     \setlogodrop{0.30ex}%
175 }

```

gentium (*Opt*)

```

176 \newcommand*{\MLX@gentium}{%
177     \setlogokern{Te}{-0.07em}%
178     \setlogokern{eX}{-0.07em}%
179     \setlogokern{La}{-.26em}%
180     \setlogokern{aT}{-.07em}%
181     \setlogokern{Xe}{-.06em}%
182     \setlogokern{eT}{-.06em}%
183     \setlogokern{eL}{-.06em}%
184     \setlogodrop{0.24ex}%
185 }

```

helvetica (*Opt*)

```

186 \newcommand*{\MLX@helvetica}{%
187     \setlogokern{Te}{-0.15em}%
188     \setlogokern{eX}{-0.08em}%
189     \setlogokern{La}{-.26em}%
190     \setlogokern{aT}{-.08em}%
191     \setlogokern{Xe}{-.07em}%

```

```

192     \setlogokern{eT}{-.15em}%
193     \setlogokern{eL}{-.04em}%
194     \setlogodrop{0.40ex}%
195 }
```

kerkis (*Opt*)

```

196 \newcommand*{\MLX@kerkis}{%
197     \setlogokern{Te}{-.02em}%
198     \setlogokern{eX}{-.02em}%
199     \setlogokern{La}{-.25em}%
200     \setlogokern{aT}{-.00em}%
201     \setlogokern{Xe}{-.00em}%
202     \setlogokern{eT}{-.10em}%
203     \setlogokern{eL}{-.05em}%
204     \setlogodrop{0.38ex}%
205 }
```

kpfonts (*Opt*)

```

206 \newcommand*{\MLX@kpfonts}{%
207     \setlogokern{Te}{-.11em}%
208     \setlogokern{eX}{-.08em}%
209     \setlogokern{La}{-.30em}%
210     \setlogokern{aT}{-.11em}%
211     \setlogokern{Xe}{-.10em}%
212     \setlogokern{eT}{-.10em}%
213     \setlogokern{eL}{-.06em}%
214     \setlogodrop{0.33ex}%
215 }
```

libertine (*Opt*) Also see **libertinus**, below.

```

216 \newcommand*{\MLX@libertine}{%
217     \setlogokern{Te}{-.05em}%
218     \setlogokern{eX}{-.06em}%
219     \setlogokern{La}{-.25em}%
220     \setlogokern{aT}{-.05em}%
221     \setlogokern{Xe}{-.05em}%
222     \setlogokern{eT}{-.05em}%
223     \setlogokern{eL}{-.02em}%
224     \setlogodrop{0.32ex}%
225 }
```

libertinus (*Opt*) There is a difference in the raised ‘A’ vs. **libertine**.

```

226 \newcommand*{\MLX@libertinus}{%
227     \setlogokern{Te}{-.05em}%
228     \setlogokern{eX}{-.06em}%
229     \setlogokern{La}{-.28em}%
230     \setlogokern{aT}{-.05em}%
231     \setlogokern{Xe}{-.05em}%
232     \setlogokern{eT}{-.05em}%
```

```

233     \setlogokern{eL}{-.02em}%
234     \setlogodrop{0.32ex}%
235 }
```

`librebodoni` (*Opt*) Specific to LibreBodoni only.

```

236 \newcommand*{\MLX@librebodoni}{%
237     \setlogokern{Te}{-0.07em}%
238     \setlogokern{eX}{-0.05em}%
239     \setlogokern{La}{-.26em}%
240     \setlogokern{aT}{-.07em}%
241     \setlogokern{Xe}{-.06em}%
242     \setlogokern{eT}{-.10em}%
243     \setlogokern{eL}{-.02em}%
244     \setlogodrop{0.49ex}%
245 }
```

`lmodern` (*Opt*)

```

246 \newcommand*{\MLX@lmodern}{%
247     \setlogokern{Te}{-0.10em}%
248     \setlogokern{eX}{-0.06em}%
249     \setlogokern{La}{-.33em}%
250     \setlogokern{aT}{-.15em}%
251     \setlogokern{Xe}{-.07em}%
252     \setlogokern{eT}{-.10em}%
253     \setlogokern{eL}{-.08em}%
254     \setlogodrop{0.52ex}%
255 }
```

`lmodernsans` (*Opt*)

```

256 \newcommand*{\MLX@lmodernsans}{%
257     \setlogokern{Te}{-0.20em}%
258     \setlogokern{eX}{-0.06em}%
259     \setlogokern{La}{-.29em}%
260     \setlogokern{aT}{-.12em}%
261     \setlogokern{Xe}{-.07em}%
262     \setlogokern{eT}{-.20em}%
263     \setlogokern{eL}{-.08em}%
264     \setlogodrop{0.45ex}%
265 }
```

`merriweather` (*Opt*)

```

266 \newcommand*{\MLX@merriweather}{%
267     \setlogokern{Te}{-0.09em}%
268     \setlogokern{eX}{-0.09em}%
269     \setlogokern{La}{-.26em}%
270     \setlogokern{aT}{-.07em}%
271     \setlogokern{Xe}{-.06em}%
272     \setlogokern{eT}{-.10em}%
273     \setlogokern{eL}{-.06em}%
274 }
```

```
274     \setlogodrop{0.32ex}%
275 }
```

newcent (Opt)

```
276 \newcommand*{\MLX@newcent}{%
277     \setlogokern{Te}{-0.08em}%
278     \setlogokern{eX}{-0.09em}%
279     \setlogokern{La}{-.30em}%
280     \setlogokern{aT}{-.07em}%
281     \setlogokern{Xe}{-.07em}%
282     \setlogokern{eT}{-.10em}%
283     \setlogokern{eL}{-.06em}%
284     \setlogodrop{0.49ex}%
285 }
```

noto (Opt)

```
286 \newcommand*{\MLX@noto}{%
287     \setlogokern{Te}{-0.11em}%
288     \setlogokern{eX}{-0.10em}%
289     \setlogokern{La}{-.30em}%
290     \setlogokern{aT}{-.07em}%
291     \setlogokern{Xe}{-.10em}%
292     \setlogokern{eT}{-.10em}%
293     \setlogokern{eL}{-.06em}%
294     \setlogodrop{0.26ex}%
295 }
```

palatino (Opt)

```
296 \newcommand*{\MLX@palatino}{%
297     \setlogokern{Te}{-0.07em}%
298     \setlogokern{eX}{-0.09em}%
299     \setlogokern{La}{-.33em}%
300     \setlogokern{aT}{-.10em}%
301     \setlogokern{Xe}{-.09em}%
302     \setlogokern{eT}{-.08em}%
303     \setlogokern{eL}{-.07em}%
304     \setlogodrop{0.35ex}%
305 }
```

pandora (Opt)

```
306 \newcommand*{\MLX@pandora}{%
307     \setlogokern{Te}{-0.09em}%
308     \setlogokern{eX}{-0.08em}%
309     \setlogokern{La}{-.32em}%
310     \setlogokern{aT}{-.07em}%
311     \setlogokern{Xe}{-.08em}%
312     \setlogokern{eT}{-.10em}%
313     \setlogokern{eL}{-.06em}%
314     \setlogodrop{0.53ex}%
315 }
```

315 }

paratype (*Opt*)

```

316 \newcommand*{\MLX@paratype}{%
317     \setlogokern{Te}{-0.07em}%
318     \setlogokern{eX}{-0.10em}%
319     \setlogokern{La}{-.26em}%
320     \setlogokern{aT}{-.07em}%
321     \setlogokern{Xe}{-.06em}%
322     \setlogokern{eT}{-.10em}%
323     \setlogokern{eL}{-.06em}%
324     \setlogodrop{0.34ex}%
325 }
```

plexserif (*Opt*)

```

326 \newcommand*{\MLX@plexserif}{%
327     \setlogokern{Te}{-0.1667em}%
328     \setlogokern{eX}{-0.125em}%
329     \setlogokern{La}{-.30em}%
330     \setlogokern{aT}{-.10em}%
331     \setlogokern{Xe}{-.125em}%
332     \setlogokern{eT}{-.16em}%
333     \setlogokern{eL}{-.10em}%
334     \setlogodrop{0.5ex}%
335 }
```

plexsans (*Opt*)

```

336 \newcommand*{\MLX@plexsans}{%
337     \setlogokern{Te}{-0.1667em}%
338     \setlogokern{eX}{-0.10em}%
339     \setlogokern{La}{-.25em}%
340     \setlogokern{aT}{-.10em}%
341     \setlogokern{Xe}{-.10em}%
342     \setlogokern{eT}{-.17em}%
343     \setlogokern{eL}{-.10em}%
344     \setlogodrop{0.5ex}%
345 }
```

quattrocento (*Opt*) Compromises must be made here. It appears that the height of `1ex` is incorrect for serif with X_{EL}ATEX, Lua_{EL}ATEX.

```

346 \newcommand*{\MLX@quattrocento}{%
347     \setlogokern{Te}{-0.09em}%
348     \setlogokern{eX}{-0.05em}%
349     \setlogokern{La}{-.26em}%
350     \setlogokern{aT}{-.07em}%
351     \setlogokern{Xe}{-.06em}%
352     \setlogokern{eT}{-.10em}%
353     \setlogokern{eL}{-.06em}%
354     \setlogodrop{.4ex}%

```

355 }

sourceserifpro (*Opt*)

```
356 \newcommand*{\MLX@sourceserifpro}{%
357     \setlogokern{Te}{-.12em}%
358     \setlogokern{eX}{-.09em}%
359     \setlogokern{La}{-.29em}%
360     \setlogokern{aT}{-.07em}%
361     \setlogokern{Xe}{-.09em}%
362     \setlogokern{eT}{-.10em}%
363     \setlogokern{eL}{-.09em}%
364     \setlogodrop{0.30ex}%
365 }
```

sourcesanspro (*Opt*)

```
366 \newcommand*{\MLX@sourcesanspro}{%
367     \setlogokern{Te}{-.12em}%
368     \setlogokern{eX}{-.09em}%
369     \setlogokern{La}{-.22em}%
370     \setlogokern{aT}{-.07em}%
371     \setlogokern{Xe}{-.09em}%
372     \setlogokern{eT}{-.10em}%
373     \setlogokern{eL}{-.09em}%
374     \setlogodrop{0.30ex}%
375 }
```

times (*Opt*)

```
376 \newcommand*{\MLX@times}{%
377     \setlogokern{Te}{-.06em}%
378     \setlogokern{eX}{-.05em}%
379     \setlogokern{La}{-.28em}%
380     \setlogokern{aT}{-.07em}%
381     \setlogokern{Xe}{-.06em}%
382     \setlogokern{eT}{-.06em}%
383     \setlogokern{eL}{-.02em}%
384     \setlogodrop{0.34ex}%
385 }
```

utopia (*Opt*)

```
386 \newcommand*{\MLX@utopia}{%
387     \setlogokern{Te}{-.08em}%
388     \setlogokern{eX}{-.04em}%
389     \setlogokern{La}{-.21em}%
390     \setlogokern{aT}{-.10em}%
391     \setlogokern{Xe}{-.02em}%
392     \setlogokern{eT}{-.10em}%
393     \setlogokern{eL}{-.06em}%
394     \setlogodrop{0.30ex}%
395 }
```

`venturis (Opt)`

```

396 \newcommand*{\MLX@venturis}{%
397     \setlogokern{Te}{-.07em}%
398     \setlogokern{eX}{-.05em}%
399     \setlogokern{La}{-.22em}%
400     \setlogokern{aT}{-.07em}%
401     \setlogokern{Xe}{-.06em}%
402     \setlogokern{eT}{-.06em}%
403     \setlogokern{eL}{-.06em}%
404     \setlogodrop{0.36ex}%
405 }
```

`vera (Opt)`

```

406 \newcommand*{\MLX@vera}{%
407     \setlogokern{Te}{-.12em}%
408     \setlogokern{eX}{-.14em}%
409     \setlogokern{La}{-.32em}%
410     \setlogokern{aT}{-.05em}%
411     \setlogokern{Xe}{-.14em}%
412     \setlogokern{eT}{-.10em}%
413     \setlogokern{eL}{-.10em}%
414     \setlogodrop{0.235ex}%
415 }
```

`verasans (Opt)`

```

416 \newcommand*{\MLX@verasans}{%
417     \setlogokern{Te}{-.12em}%
418     \setlogokern{eX}{-.10em}%
419     \setlogokern{La}{-.28em}%
420     \setlogokern{aT}{-.05em}%
421     \setlogokern{Xe}{-.10em}%
422     \setlogokern{eT}{-.10em}%
423     \setlogokern{eL}{-.10em}%
424     \setlogodrop{0.35ex}%
425 }
```

3.2.1 Common synonyms

Synonyms for commonly-used fonts.

`tgbonum (Opt)`

```
426 \newcommand*{\MLX@tgbonum}{\MLX@bookman}
```

`tgheros (Opt)`

```
427 \newcommand*{\MLX@tgheros}{\MLX@helvetica}
```

`tgpagella (Opt)`

```
428 \newcommand*{\MLX@tgpagella}{\MLX@palatino}
```

tgschola (*Opt*)

```
429 \newcommand*{\MLX@tgschola}{\MLX@newcent}
```

tgtermes (*Opt*)

```
430 \newcommand*{\MLX@tgtermes}{\MLX@times}
```

3.2.2 Similar fonts

The following work well enough that a separate definition is probably not necessary.

antiqua (*Opt*)

```
431 \newcommand*{\MLX@antiqua}{\MLX@baskerville}
```

anttor (*Opt*)

```
432 \newcommand*{\MLX@anttor}{\MLX@antpolt}
```

artemisia (*Opt*)

```
433 \newcommand*{\MLX@artemisia}{\MLX@baskerville}
```

caladea (*Opt*)

```
434 \newcommand*{\MLX@caladea}{\MLX@baskerville}
```

caslon (*Opt*)

```
435 \newcommand*{\MLX@caslon}{\MLX@baskerville}
```

cochineal (*Opt*)

```
436 \newcommand*{\MLX@cochineal}{\MLX@baskerville}
```

concmath (*Opt*)

```
437 \newcommand*{\MLX@concmath}{\MLX@lmodern}
```

drm (*Opt*)

```
438 \newcommand*{\MLX@drm}{\MLX@lmodern}
```

garamond (*Opt*)

```
439 \newcommand*{\MLX@garamond}{\MLX@baskerville}
```

`imfellenglish (Opt)`

```
440 \newcommand*{\MLX@imfellenglish}{\MLX@baskerville}
```

`literat (Opt)`

```
441 \newcommand*{\MLX@literat}{\MLX@baskerville}
```

`roboto (Opt)`

```
442 \newcommand*{\MLX@roboto}{\MLX@pandora}
```

`romande (Opt)`

```
443 \newcommand*{\MLX@romande}{\MLX@baskerville}
```

3.3 Manual adjust selection

`\adjustlogos {⟨package option⟩}`

If the given option matches a predefined `\MLX@...` macro, use it.

```
444 \newcommand*{\adjustlogos}[1]{%
445   \ifcsdef{MLX@#1}{%
446     \PackageInfo{metalogox}{Setting #1}%
447     \csuse{MLX@#1}%
448   }{%
449     \PackageError{metalogox}{Unknown setting #1}%
450     {See the metalogox documentation for a list of options.}%
451   }%
452 }
```

3.4 Font detection

`MLX@@foundfont (bool)` Found the font?

```
453 \newbool{\MLX@@foundfont}
```

`\MLX@@detectvariant {⟨1:family⟩} {⟨2:variant⟩} {⟨3:name⟩} {⟨4:setting⟩}`

If the font variant matches, adjust accordingly.

(The doubled @ is to distinguish this from a valid metalogox option.)

```
454 \newcommand*{\MLX@@detectvariant}[4]{%
455 \ifdefstring{\MLX@@thisfont}{#1#2}{%
456   \booltrue{\MLX@@foundfont}%
457   \PackageInfo{metalogox}{Detected #1#2, #3. Using #4}%
458 }
```

```

458     \adjustlogos{#4}%
459 }{ }%
460 }

\MLX@@detectone {⟨1: family⟩} {⟨2: name⟩} {⟨3: setting⟩}

```

Tests variants. If a font family and variant matches, select the `metalogox` option.

(The doubled @ is to distinguish this from a valid `metalogox` option.)

```

461 \NewDocumentCommand{\MLX@@detectone}{m m m}{%
462 \MLX@@detectvariant{#1}{}{#2}{#3}%
463 \MLX@@detectvariant{#1}{-TLF}{#2}{#3}%
464 \MLX@@detectvariant{#1}{-LF}{#2}{#3}%
465 \MLX@@detectvariant{#1}{-OsF}{#2}{#3}%
466 \MLX@@detectvariant{#1}{-TOSF}{#2}{#3}%
467 \MLX@@detectvariant{#1}{Condensed-TLF}{#2}{#3}%
468 \MLX@@detectvariant{#1}{Condensed-LF}{#2}{#3}%
469 \MLX@@detectvariant{#1}{Condensed-OsF}{#2}{#3}%
470 \MLX@@detectvariant{#1}{Condensed-TOSF}{#2}{#3}%
471 \MLX@@detectvariant{#1}{(0)}{#2}{#3}%
472 \MLX@@detectvariant{#1}{(1)}{#2}{#3}%
473 }

```

```
\autoadjustlogos *
```

Search a list of fonts and variants, looking for a match with the current one.

```
474 \NewDocumentCommand{\autoadjustlogos}{s}{%
```

Not yet discovered the font:

```
475 \boolfalse{MLX@@foundfont}%
```

If starred, use the text body font, else use the local font:

```

476 \IfBooleanTF{#1}{%
477     \edef\MLX@@thisfont{\familydefault}%
478 }{%
479     \edef\MLX@@thisfont{\f@family}%
480 }

```

Announce the desired font:

```
481 \PackageInfo{metalogox}{Searching for \MLX@@thisfont}%
```

Default if nothing is found:

```
482 \adjustlogos{lmodern}%
```

Search a list of possibilities:

```
483 \MLX@@detectone{AccanthisADFStdNoThree}{accanthis}{accanthis}%
484 \MLX@@detectone{AccanthisADFStdNo3}{accanthis}{accanthis}%
485 \MLX@@detectone{Alegreya}{Alegreya}{alegreya}%
486 \MLX@@detectone{AlegreyaSans}{AlegreyaSans}{alegreya}%
487 \MLX@@detectone{AlgolRevived}{algolrevived}{algolrevived}%
488 \MLX@@detectone{uaq}{antiqua}{baskerville}%
489 \MLX@@detectone{antp}{antpolt}{antpolt}%
490 \MLX@@detectone{AntykwaPoltawskiego}{antpolt}{antpolt}%
491 \MLX@@detectone{antt}{anttor}{antpolt}%%
492 \MLX@@detectone{AntykwaTorunska}{anttor}{antpolt}%
493 \MLX@@detectone{ArchivZero}{Archiv0}{helvetica}%
494 \MLX@@detectone{Archiv0}{Archiv0}{helvetica}%
495 \MLX@@detectone{arsenal}{Arsenal}{alegreya}%
496 \MLX@@detectone{fav}{arev}{vera}%
497 \MLX@@detectone{Arimo}{Arimo}{helvetica}%
498 \MLX@@detectone{atkinsn}{Atkinson Hyperlegible}{helvetica}%
499 \MLX@@detectone{AtkinsonHyperlegible}{Atkinson Hyperlegible}{helvetica}%
500 \MLX@@detectone{pag}{Avant Garde}{avantgarde}%
501 \MLX@@detectone{qag}{tgadventor}{avantgarde}%
502 \MLX@@detectone{ybv}{baskervald}{baskerville}%
503 \MLX@@detectone{ybwv}{baskervald}{baskerville}%
504 \MLX@@detectone{Baskervaldx}{Baskervaldx}{baskerville}%
505 \MLX@@detectone{BaskervilleF}{Baskervillef}{baskerville}%
506 \MLX@@detectone{fve}{beraserif}{vera}%
507 \MLX@@detectone{fvs}{berasans}{verasans}%
508 \MLX@@detectone{ybd}{berenis}{berenis}%
509 \MLX@@detectone{ybd2}{berenis}{berenis}%
510 \MLX@@detectone{ybd2j}{berenis}{berenis}%
511 \MLX@@detectone{ybdj}{berenis}{berenis}%
512 \MLX@@detectone{BerenisADFFPro}{berenis}{berenis}%
513 \MLX@@detectone{LinuxBiolinumT}{biolinum}{helvetica}%
514 \MLX@@detectone{Cabin}{Cabin}{helvetica}%
515 \MLX@@detectone{CabinCondensed}{CabinCondensed}{helvetica}%
516 \MLX@@detectone{Caladea}{caladea}{baskerville}%
517 \MLX@@detectone{cantarell}{cantarell}{helvetica}%
518 \MLX@@detectone{Crlt}{Carlito}{crimson}%
519 \MLX@@detectone{Carlito}{Carlito}{crimson}%
520 \MLX@@detectone{charssil}{CharisSIL}{times}%
521 \MLX@@detectone{CharisSIL}{CharisSIL}{times}%
522 \MLX@@detectone{mdbch}{mdbch - Math Design Bitstream Charter}{charter}%
523 \MLX@@detectone{Chivo}{Chivo}{helvetica}%
524 \MLX@@detectone{ClearSans}{Clear Sans}{helvetica}%
525 \MLX@@detectone{Cochineal}{cochineal}{baskerville}%
526 \MLX@@detectone{Coelacanth}{coelacanth}{coelacanth}%
527 \MLX@@detectone{comfortaa}{comfortaa}{avantgarde}%
528 \MLX@@detectone{ComicNeue}{comicneue}{avantgarde}%
529 \MLX@@detectone{cmbr}{Computer Modern Bright}{lmodern}%
530 \MLX@@detectone{lcmss}{Computer Modern Sans Quote}{lmodern}%
531 \MLX@@detectone{cmr}{Computer Modern Roman}{lmodern}%
532 \MLX@@detectone{cmss}{Computer Modern Sans}{lmodernsans}%
533 \MLX@@detectone{ccr}{concmath}{lmodern}%
534 \MLX@@detectone{CormorantGaramond}{CormorantGaramond}{garamond}%
535 \MLX@@detectone{Crimson}{crimson}{crimson}%
536 \MLX@@detectone{CrimsonPro}{CrimsonPro}{crimson}%
```

```
537 \MLX@@detectone{cpr}{Cuprum}{utopia}%
538 \MLX@@detectone{Cuprum}{Cuprum}{utopia}%
539 \MLX@@detectone{cyklop}{Cyklop}{lmodern}%
540 \MLX@@detectone{DejaVuSerif}{DejaVuSerif}{vera}%
541 \MLX@@detectone{DejaVuSerifCondensed}{DejaVuSerif Condensed}{vera}%
542 \MLX@@detectone{DejaVuSans}{DejaVuSans}{verasans}%
543 \MLX@@detectone{drm}{DRM}{lmodern}%
544 \MLX@@detectone{droidserif}{Droid Serif}{droidserif}%%
545 \MLX@@detectone{droidsans}{Droid Sans}{droidsans}%%
546 \MLX@@detectone{DroidSerif}{Droid Serif}{droidserif}%%
547 \MLX@@detectone{DroidSans}{Droid Sans}{droidsans}%%
548 \MLX@@detectone{EBGaramond}{EB Garamond}{garamond}%
549 \MLX@@detectone{EBGaramond12}{EB Garamond}{garamond}%
550 \MLX@@detectone{Eczar}{Eczar}{times}%
551 \MLX@@detectone{erewhon}{erewhon}{utopia}%
552 \MLX@@detectone{Erewhon}{erewhon}{utopia}%
553 \MLX@@detectone{fbb}{fbb}{baskerville}%
554 \MLX@@detectone{FiraSans}{Fira Sans}{helvetica}%
555 \MLX@@detectone{FiraSansBook}{Fira Sans}{helvetica}%
556 \MLX@@detectone{FiraSansThin}{Fira Sans}{helvetica}%
557 \MLX@@detectone{FiraSansLight}{Fira Sans}{helvetica}%
558 \MLX@@detectone{FiraSansExtraLight}{Fira Sans}{helvetica}%
559 \MLX@@detectone{FiraSansUltraLight}{Fira Sans}{helvetica}%
560 \MLX@@detectone{futs}{fourier}{utopia}%
561 \MLX@@detectone{fnc}{fouriernc}{newcent}%
562 \MLX@@detectone{gentium}{gentium}{gentium}%
563 \MLX@@detectone{GentiumPlus}{gentium}{gentium}%
564 \MLX@@detectone{artemisia}{gfsartemisia}{baskerville}%
565 \MLX@@detectone{GFSArtemisia}{gfsartemisia}{baskerville}%
566 \MLX@@detectone{artemisiaeuler}{gfsartemisia}{baskerville}%
567 \MLX@@detectone{bodoni}{gfsbodoni}{bodoni}%
568 \MLX@@detectone{GFSBodoni}{gfsbodoni}{bodoni}%
569 \MLX@@detectone{udidot}{gfsdidot}{didot}%
570 \MLX@@detectone{FreeSerif}{GNU Freeserif}{times}%
571 \MLX@@detectone{FreeSans}{GNU Freesans}{helvetica}%
572 \MLX@@detectone{neohellenic}{GFS Neoheellenic}{helvetica}%
573 \MLX@@detectone{GFSNeohellenic}{GFS Neoheellenic}{helvetica}%
574 \MLX@@detectone{Gillius}{Gillius}{avantgarde}%
575 \MLX@@detectone{GilliusADF}{Gillius}{avantgarde}%
576 \MLX@@detectone{GilliusADFCond}{Gillius}{avantgarde}%
577 \MLX@@detectone{GilliusADFNo2}{Gillius}{avantgarde}%
578 \MLX@@detectone{GilliusADFNo2Cond}{Gillius}{avantgarde}%
579 \MLX@@detectone{Go}{Go Sans}{helvetica}%
580 \MLX@@detectone{phv}{helvet}{helvetica}%
581 \MLX@@detectone{Heuristica}{heuristic}{utopia}%
582 \MLX@@detectone{heuristic}{heuristic}{utopia}%
583 \MLX@@detectone{IbarraRealNova}{Ibarra}{times}%
584 \MLX@@detectone{IMFELLEnglish}{imfellEnglish}{baskerville}%
585 \MLX@@detectone{InriaSans}{Inria Sans}{helvetica}%
586 \MLX@@detectone{InriaSerif}{Inria Serif}{baskerville}%
587 \MLX@@detectone{Inter}{Inter}{helvetica}%
588 \MLX@@detectone{iwona}{Iwona}{helvetica}%
589 \MLX@@detectone{Iwona}{Iwona}{helvetica}%
590 \MLX@@detectone{IwonaLight}{Iwona}{helvetica}%
```

```
591 \MLX@@detectone{IwonaMedium}{Iwona}{helvetica}%
592 \MLX@@detectone{IwonaHeavy}{Iwona}{helvetica}%
593 \MLX@@detectone{IwonaCond}{Iwona}{helvetica}%
594 \MLX@@detectone{IwonaCondLight}{Iwona}{helvetica}%
595 \MLX@@detectone{IwonaCondMedium}{Iwona}{helvetica}%
596 \MLX@@detectone{IwonaCondHeavy}{Iwona}{helvetica}%
597 \MLX@@detectone{Junicode}{Junicode}{times}%
598 \MLX@@detectone{mak}{kerkis}{kerkis}%
599 \MLX@@detectone{maksf}{kerkis sans}{kerkis}%
600 \MLX@@detectone{jkp}{kpfonts}{kpfonts}%
601 \MLX@@detectone{jkpf}{kpfonts}{kpfonts}%
602 \MLX@@detectone{jkpfosn}{kpfonts}{kpfonts}%
603 \MLX@@detectone{jkpk}{kpfonts}{kpfonts}%
604 \MLX@@detectone{jkpkf}{kpfonts}{kpfonts}%
605 \MLX@@detectone{jkpkfosn}{kpfonts}{kpfonts}%
606 \MLX@@detectone{jkpkos}{kpfonts}{kpfonts}%
607 \MLX@@detectone{jkpkosn}{kpfonts}{kpfonts}%
608 \MLX@@detectone{jkpkvos}{kpfonts}{kpfonts}%
609 \MLX@@detectone{jkpl}{kpfonts}{kpfonts}%
610 \MLX@@detectone{jkplf}{kpfonts}{kpfonts}%
611 \MLX@@detectone{jkplfosn}{kpfonts}{kpfonts}%
612 \MLX@@detectone{jkplk}{kpfonts}{kpfonts}%
613 \MLX@@detectone{jkplkf}{kpfonts}{kpfonts}%
614 \MLX@@detectone{jkplkfosn}{kpfonts}{kpfonts}%
615 \MLX@@detectone{jkplkos}{kpfonts}{kpfonts}%
616 \MLX@@detectone{jkplkosn}{kpfonts}{kpfonts}%
617 \MLX@@detectone{jkplkvos}{kpfonts}{kpfonts}%
618 \MLX@@detectone{jkpllos}{kpfonts}{kpfonts}%
619 \MLX@@detectone{jkplosn}{kpfonts}{kpfonts}%
620 \MLX@@detectone{jkplvlos}{kpfonts}{kpfonts}%
621 \MLX@@detectone{jkpos}{kpfonts}{kpfonts}%
622 \MLX@@detectone{jkposn}{kpfonts}{kpfonts}%
623 \MLX@@detectone{jkps}{kpfonts}{kpfonts}%
624 \MLX@@detectone{jkpsff}{kpfonts}{kpfonts}%
625 \MLX@@detectone{jkpsffosn}{kpfonts}{kpfonts}%
626 \MLX@@detectone{jkpsks}{kpfonts}{kpfonts}%
627 \MLX@@detectone{jkpsksf}{kpfonts}{kpfonts}%
628 \MLX@@detectone{jkpsksfosn}{kpfonts}{kpfonts}%
629 \MLX@@detectone{jkpsksos}{kpfonts}{kpfonts}%
630 \MLX@@detectone{jkpsksosn}{kpfonts}{kpfonts}%
631 \MLX@@detectone{jkpssskvos}{kpfonts}{kpfonts}%
632 \MLX@@detectone{jkpsssos}{kpfonts}{kpfonts}%
633 \MLX@@detectone{jkpsssosn}{kpfonts}{kpfonts}%
634 \MLX@@detectone{jkpsssvos}{kpfonts}{kpfonts}%
635 \MLX@@detectone{jkptt}{kpfonts}{kpfonts}%
636 \MLX@@detectone{jkpttos}{kpfonts}{kpfonts}%
637 \MLX@@detectone{jkpttosn}{kpfonts}{kpfonts}%
638 \MLX@@detectone{jkpttvos}{kpfonts}{kpfonts}%
639 \MLX@@detectone{jkpvos}{kpfonts}{kpfonts}%
640 \MLX@@detectone{jkpx}{kpfonts}{kpfonts}%
641 \MLX@@detectone{jkpxf}{kpfonts}{kpfonts}%
642 \MLX@@detectone{jkpxffosn}{kpfonts}{kpfonts}%
643 \MLX@@detectone{jkpxk}{kpfonts}{kpfonts}%
644 \MLX@@detectone{jkpxkf}{kpfonts}{kpfonts}%
```

```
645 \MLX@@detectone{jkpxkfosn}{kpfonts}{kpfonts}%
646 \MLX@@detectone{jkpxkos}{kpfonts}{kpfonts}%
647 \MLX@@detectone{jkpxkosn}{kpfonts}{kpfonts}%
648 \MLX@@detectone{jkpxkvos}{kpfonts}{kpfonts}%
649 \MLX@@detectone{jkpxos}{kpfonts}{kpfonts}%
650 \MLX@@detectone{jkpxosn}{kpfonts}{kpfonts}%
651 \MLX@@detectone{jkpxvos}{kpfonts}{kpfonts}%
652 \MLX@@detectone{JosefinSans}{Josefin}{lmodern}%
653 \MLX@@detectone{kurier}{Kurier}{helvetica}%
654 \MLX@@detectone{Kurier}{Kurier}{helvetica}%
655 \MLX@@detectone{KurierLight}{Kurier}{helvetica}%
656 \MLX@@detectone{KurierMedium}{Kurier}{helvetica}%
657 \MLX@@detectone{KurierHeavy}{Kurier}{helvetica}%
658 \MLX@@detectone{KurierCond}{Kurier}{helvetica}%
659 \MLX@@detectone{KurierCondLight}{Kurier}{helvetica}%
660 \MLX@@detectone{KurierCondMedium}{Kurier}{helvetica}%
661 \MLX@@detectone{KurierCondHeavy}{Kurier}{helvetica}%
662 \MLX@@detectone{lato}{Lato}{helvetica}%
663 \MLX@@detectone{Lato}{Lato}{helvetica}%
664 \MLX@@detectone{lmr}{lmodern}{lmodern}%
665 \MLX@@detectone{mlmr}{MLModern}{lmodern}%
666 \MLX@@detectone{lmss}{MLModern}{lmodern}%
667 \MLX@@detectone{lmss}{lmodern sans}{lmodernsans}%
668 \MLX@@detectone{lmssq}{lmodern sans}{lmodernsans}%
669 \MLX@@detectone{LatinModernRoman}{Latin Modern Roman}{lmodern}%
670 \MLX@@detectone{LatinModernSans}{Latin Modern Sans}{lmodernsans}%
671 \MLX@@detectone{LinuxLibertineT}{libertine}{libertine}%
672 \MLX@@detectone{LinLibertine}{libertine}{libertine}%
673 \MLX@@detectone{LinBiolinum}{libertine}{helvetica}%
674 \MLX@@detectone{LibertinusSerif}{libertinus-type1}{libertinus}%
675 \MLX@@detectone{LibertinusSans}{libertinus-type1}{helvetica}%
676 \MLX@@detectone{libertinusserif}{libertinus-otf}{libertinus}%
677 \MLX@@detectone{libertinussans}{libertinus-otf}{helvetica}%
678 \MLX@@detectone{LibreBskv1}{librebaskerville}{baskerville}%
679 \MLX@@detectone{LibreBaskerville}{librebaskerville}{baskerville}%
680 \MLX@@detectone{LibreBodoni}{LibreBodoni}{librebodoni}%
681 \MLX@@detectone{LibreCaslonText}{Libre Caslon}{baskerville}%
682 \MLX@@detectone{LibreCsln}{Libre Caslon}{baskerville}%
683 \MLX@@detectone{lyl}{libris}{avantgarde}%
684 \MLX@@detectone{llcmss}{LX Fonts}{avantgarde}%
685 \MLX@@detectone{ptm}{mathptmx}{times}%
686 \MLX@@detectone{ppl}{mathpazo}{palatino}%
687 \MLX@@detectone{bch}{mdbch}{charter}%
688 \MLX@@detectone{mdput}{mdput - Math Design Utopia}{utopia}%
689 \MLX@@detectone{mdugm}{mdugm - Math Design URW Garamond}{baskerville}%
690 \MLX@@detectone{Merriwthr}{merriweather}{merriweather}%
691 \MLX@@detectone{MerriwthrSans}{merriweather}{merriweather}%
692 \MLX@@detectone{Merriweather}{merriweather}{merriweather}%
693 \MLX@@detectone{MerriweatherSans}{merriweather}{merriweather}%
694 \MLX@@detectone{MintSpirit}{Mint Spirit}{avantgarde}%
695 \MLX@@detectone{MintSpiritNoTwo}{Mint Spirit No 2}{avantgarde}%
696 \MLX@@detectone{MintSpiritNo2}{Mint Spirit No 2}{avantgarde}%
697 \MLX@@detectone{Montserrat}{Montserrat}{helvetica}%
698 \MLX@@detectone{MontserratAlternates}{Montserrat}{helvetica}%
```

```
699 \MLX@@detectone{pnc}{newcent}{newcent}%
700 \MLX@@detectone{zpltlf}{newpxtext}{palatino}%
701 \MLX@@detectone{minntx}{newtxtext}{times}%
702 \MLX@@detectone{ntxtlf}{newtxtext}{times}%
703 \MLX@@detectone{nimbussans}{nimbussans}{helvetica}%
704 \MLX@@detectone{NimbusSans}{nimbusserif}{helvetica}%
705 \MLX@@detectone{NimbusSerif}{nimbusserif}{times}%
706 \MLX@@detectone{NimbusSansL}{nimbussans}{helvetica}%
707 \MLX@@detectone{ztm}{nimbusserif}{times}%
708 \MLX@@detectone{zhv}{nimbussans}{helvetica}%
709 \MLX@@detectone{NotoSerif}{noto}{noto}%
710 \MLX@@detectone{NotoSans}{noto}{noto}%
711 \MLX@@detectone{Nunito}{Nunito}{helvetica}%
712 \MLX@@detectone{OldStandard}{Old Standard}{didot}%
713 \MLX@@detectone{fosj}{opensans}{avantgarde}%
714 \MLX@@detectone{opensans}{opensans}{avantgarde}%
715 \MLX@@detectone{OpenSans}{Open Sans}{avantgarde}%
716 \MLX@@detectone{Zeroswald}{Oswald}{utopia}%
717 \MLX@@detectone{Ovrlick}{Overlock}{avantgarde}%
bug with XeLaTeX%
718 \MLX@@detectone{Overlock}{Overlock}{avantgarde}%
bug with XeLaTeX%
719 \MLX@@detectone{panr}{pandora}{pandora}%
720 \MLX@@detectone{pss}{pandora}{pandora}%
721 \MLX@@detectone{PTSerif}{paratype}{paratype}%
722 \MLX@@detectone{PTSans}{paratype}{paratype}%
723 \MLX@@detectone{PTSansNarrow}{paratype}{paratype}%
724 \MLX@@detectone{IBMPlexSerif}{plex-serif}{plexserif}%
725 \MLX@@detectone{IBMPlexSans}{plex-sans}{plexsans}%
726 \MLX@@detectone{pxr}{pxfonts}{palatino}%
727 \MLX@@detectone{pxss}{pxfonts}{helvetica}%
728 \MLX@@detectone{Quattro}{quattrocento}{quattrocento}%
729 \MLX@@detectone{QuattroSans}{quattrocento}{quattrocento}%
730 \MLX@@detectone{Quattrocento}{quattrocento}{quattrocento}%
731 \MLX@@detectone{QuattrocentoSans}{quattrocento}{quattrocento}%
732 \MLX@@detectone{Raleway}{raleway}{helvetica}%
733 \MLX@@detectone{Roboto}{roboto}{helvetica}%
734 \MLX@@detectone{RobotoSlab}{roboto}{roboto}%
735 \MLX@@detectone{RobotoCondensed}{roboto}{helvetica}%
736 \MLX@@detectone{yrd}{romande}{baskerville}%
737 \MLX@@detectone{yrd}{romande}{baskerville}%
738 \MLX@@detectone{yrdw}{romande}{baskerville}%
todo swash style%
739 \MLX@@detectone{yrdaw}{romande}{baskerville}%
todo swash style%
740 \MLX@@detectone{Shobhika}{Shobhika}{paratype}%
741 \MLX@@detectone{SourceSerifPro}{sourceserifpro}{sourcereserifpro}%
742 \MLX@@detectone{SourceSansPro}{sourcesanspro}{sourcesanspro}%
743 \MLX@@detectone{SticksTooText}{stickstootext}{times}%
744 \MLX@@detectone{stix}{stix}{times}%
745 \MLX@@detectone{stix2}{stix2}{times}%
746 \MLX@@detectone{STIXTwoText}{stix2}{times}%
747 \MLX@@detectone{pbk}{bookman}{bookman}%
748 \MLX@@detectone{qbk}{tgbonum}{bookman}%
749 \MLX@@detectone{qhv}{tgheros}{helvetica}%
750 \MLX@@detectone{qpl}{tgpagella}{palatino}%
751 \MLX@@detectone{qcs}{tgschola}{newcent}%
752 \MLX@@detectone{qtm}{tgtermes}{times}%
```

```

753 \MLX@@detectone{TeXGyreAdventor}{TeX Gyre Adventor}{avantgarde}%
754 \MLX@@detectone{TeXGyreBonom}{TeX Gyre Bonum}{bookman}%
755 \MLX@@detectone{TeXGyreHeros}{TeX Gyre Heros}{helvetica}%
756 \MLX@@detectone{TeXGyrePagella}{TeX Gyre Pagella}{palatino}%
757 \MLX@@detectone{TeXGyreSchola}{TeX Gyre Schola}{newcent}%
758 \MLX@@detectone{TeXGyreTermes}{TeX Gyre Termes}{times}%
759 \MLX@@detectone{txr}{txfonts}{times}%
760 \MLX@@detectone{txss}{txfonts}{times}%
761 \MLX@@detectone{UniversalisADFStd}{Universalis ADF Std}{crimson}%
762 \MLX@@detectone{ugq}{URW Grotesk}{crimson}%
763 \MLX@@detectone{put}{utopia}{utopia}%
764 \MLX@@detectone{yvt}{venturis}{venturis}%
765 \MLX@@detectone{yvtj}{venturis}{venturis}%
766 \MLX@@detectone{yvtw}{venturis}{venturis}%
767 \MLX@@detectone{yvtjw}{venturis}{venturis}%
768 \MLX@@detectone{yvtaw}{venturis}{venturis}%
769 \MLX@@detectone{yvtajw}{venturis}{venturis}%
770 \MLX@@detectone{yv1}{venturisans}{venturis}%
771 \MLX@@detectone{yv2}{venturi2}{venturis}%
772 \MLX@@detectone{yv3}{venturi2}{venturis}%
773 \MLX@@detectone{yvo}{venturisold}{venturis}%
774 \MLX@@detectone{yvoa}{venturisold}{venturis}%
775 \MLX@@detectone{XCharter}{XCharter}{charter}%
776 \MLX@@detectone{XITS}{XITS}{times}%

```

Warning if font was not found:

```

777 \ifbool{\MLX@@foundfont}%
778     {}%
779     {%
780         \PackageWarningNoLine{metalogox}%
781             {%
782                 Did not find font \MLX@@thisfont.\MessageBreak%
783                 To improve \string\LaTeX, and related logos:\MessageBreak%
784                 \string\usepackage[option]{metalogox}\MessageBreak%
785                 Common options: times, bookman for serif,\MessageBreak%
786                 helvetica, avantgarde for sans%
787             }%
788     }%
789 }

```

3.5 Option declaration

```

790 \DeclareOption*{%
791     \adjustlogos{\CurrentOption}%
792 }

```

3.6 Default settings

Adjust according to the text body font, if detected, or use defaults otherwise:

```
793 \autoadjustlogos*
```

3.7 Option trigger

Any metalogox package option will next override the above settings.

```
794 \ProcessOptions\relax
```

3.8 Support for the hologo and hvlogos packages

If hologo is used, a few macros are defined to use metalogo kerning. (hvlogos uses hologo, so is also supported.)

```
795 \AtBeginDocument{  
796  
797 \IfPackageLoadedTF{hologo}  
798 {  
799 \def\HoLogo@TeX#1{\TeX}  
800  
801 \def\HoLogo@La#1{  
802   \o@x1@everylogo  
803   L\kern\xl@kern@La@La  
804   {\ifxetex  
805     \XeTeXuseglyphmetrics@ne  
806   \fi  
807   \sbox{z@ T}  
808   \sbox{one{xl@LaTeX@a}}%  
809   \vbox to\ht{z@{  
810     \hbox{  
811       \ltx@sh@ft{\ht{z@}}%  
812       \xl@sh@ft{\ht{one}}%  
813       \xl@LaTeX@a  
814       \xl@sh@ft{\ht{z@}}%  
815       \ltx@sh@ft{\ht{one}}}%  
816   \vss}}%  
817 }  
818  
819 \def\HoLogo@LaTeX#1{\HoLogo@La{La}\kern\xl@kern@LaTeX@aT\TeX}  
820  
821 \def\HoLogo@LaTeXe#1{  
822   \hologo{LaTeX}}%  
823   \kern\xl@kern@LaTeXe@Xii%  
824   \hbox{  
825     \HOLOGO@MathSetup  
826     2%  
827     $_{\textstyle\backslash varepsilon}$%  
828 }%  
829 }  
830  
831 \def\HoLogo@LaTeXTeX#1{  
832   (%  
833   \kern\xl@kern@LaTeX@aT  
834   \hologo{La}}%
```

```
835     \kern\xl@kern@LaTeX@aT
836  )%
837     \kern\xl@kern@LaTeX@aT
838 \hologo{TeX}%
839 }
840 \expandafter\let\csname HoLogo@LaTeX\endcsname\HoLogo@LaTeXTeX
841
842 \def\HoLogo@XeTeX#1{\Xe\kern\xl@kern@XeTeX@eT\TeX}
843
844 \def\HoLogo@XeLaTeX#1{\Xe\kern\xl@kern@XeLaTeX@eL\LaTeX}
845
846 }
847 {}% hologo not loaded
848
849 }% AtBeginDocument
```

A Change History

v1.00		Warning if font was not found.	24
General: 2019/01/20 Initial version.	1	\MLX@@detectvariant: Warning if	
v1.01		font was not found.	17
General: 2023/01/03	1	v1.04	
Docs adjusted for dtxdescribe.	1	General: 2024/01/26	1
Updated L ^A T _E X Font Catalog		Added support for holo, hvlogos.	25
website.	1	v1.05	
v1.02		General: 2024/03/01	1
General: 2024/01/12	1	\autoadjustlogos: Fixed Erewhon.	18
Updated contact info.	1	v1.06	
v1.03		General: 2024/03/07	1
General: 2024/01/19	1	\autoadjustlogos: Improved	
Added Atkinson Hyperlegible,		detection of Archiv0, Atkinson	
Charis SIL, Cuprum, Eczar, Ibarra,		Hyperlegible, Cuprum, Eczar,	
Inria, Inter, MLModern, Nunito,		Ibarra, Nunito.	18
Oswald.	1	v1.07	
Improved TOC change log and		General: xpars only if old format.	5
index entries.	1	2025/01/23	1
Warning if font was not found.	17	\autoadjustlogos: Added arsenal.	18
\autoadjustlogos: Updated many			
fonts for changed family names. .	18		

B Index

A		charter (option)	8
accanthis (option)	cochineal (option)	16
\adjustlogos	coelacanth (option)	8
alegreya (option)	concmath (option)	16
algolrevived (option)	crimson (option)	8
antiqua (option)	D	
antpol (option)	default (option)	5
anttor (option)	didot (option)	8
artemisia (option)	drm (option)	16
\autoadjustlogos	droidsans (option)	9
\autoadjustlogos _U *	droidserif (option)	9
avantgarde (option)	G	
		garamond (option)	16
		gentium (option)	9
B		H	
baskerville (option)	helvetica (option)	9
berenis (option)		
bodoni (option)		
boisik (option)		
bookman (option)		
Booleans:		I	
MLX@@foundfont	imfellenglish (option)	17
C		K	
caladea (option)	kerkis (option)	10
caslon (option)	kpffonts (option)	10

	L		
libertine (option)	10	librebodoni	11
libertinus (option)	10	literat	17
librebodoni (option)	11	lmodern	11
literat (option)	17	lmodernsans	11
lmodern (option)	11	merriweather	11
lmodernsans (option)	11	newcent	12
	M		
merriweather (option)	11	noto	12
metalogox (package)	3	palatino	12
\MLX@@detectone	461	pandora	12
\MLX@@detectvariant	454	paratype	13
MLX@@foundfont (boolean)	17	plexsans	13
	N		
newcent (option)	12	plexserif	13
noto (option)	12	quattrocento	13
	O		
Options:		roboto	17
accanthis	5	romande	17
alegreya	5	sourcesanspro	14
algorrevived	6	sourceserifpro	14
antiqua	16	tgbonum	15
antpolt	6	tgheros	15
anttor	16	tgpagella	15
artemisia	16	tgschola	16
avantgarde	6	tgtermes	16
baskerville	6	times	14
berenis	7	utopia	14
bodoni	7	venturis	15
boisik	7	vera	15
bookman	7	verasans	15
caladea	16		
caslon	16	P	
charter	8	Packages:	
cochineal	16	metalogox	3
coelacanth	8	palatino (option)	12
concmath	16	pandora (option)	12
crimson	8	paratype (option)	13
default	5	plexsans (option)	13
didot	8	plexserif (option)	13
drm	16		
droidsans	9	Q	
droidserif	9	quattrocento (option)	13
garamond	16		
gentium	9	R	
helvetica	9	roboto (option)	17
imfellenglish	17	romande (option)	17
kerkis	10		
kpfonts	10	S	
libertine	10	sourcesanspro (option)	14
libertinus	10	sourceserifpro (option)	14
	T		
		tgbonum (option)	15
		tgheros (option)	15
		tgpagella (option)	15
		tgschola (option)	16
		tgtermes (option)	16
		times (option)	14

U	V
<i>venturis</i> (option)	<i>15</i>
<i>vera</i> (option)	<i>15</i>
<i>utopia</i> (option)	<i>14</i>
<i>verasans</i> (option)	<i>15</i>