

The `enparen` package

Heiko Oberdiek*

2016/05/16 v1.1

Abstract

The package defines macros to set parentheses that automatically change the symbols from inner to outer fences.

Contents

1 Documentation	1
1.1 User macros	2
1.2 Contexts	3
1.3 Options	3
1.4 Notes	3
2 Implementation	4
2.1 Resources	4
2.2 Contexts	4
2.2.1 Stack for contexts	4
2.2.2 Context user macros	5
2.3 Symbols	6
2.4 Main user macros	6
2.5 Options	7
2.6 Context settings	8
2.7 At end of document	8
3 Installation	9
3.1 Download	9
3.2 Bundle installation	9
3.3 Package installation	9
3.4 Refresh file name databases	10
3.5 Some details for the interested	10
4 References	10
5 History	10
[2012/01/07 v1.0]	10
[2016/05/16 v1.1]	10
6 Index	10

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

The L^AT_EX package provides macros for automatically changed parentheses symbols depending on the fence order. The innermost parentheses are always using the same parentheses. The symbols changes for the outer fences.

Example:

```
{a (b) [c (d)] (e)}
```

is generated by

```
\documentclass{article}
\usepackage{enparen}
\begin{document}
\enparen{a \enparen{b} \enparen{c \enparen{d}} \enparen{e}}
\end{document}
```

The package is the result of a newsgroup thread. Dan gives the following specification [1]:

“On the other hand, the rules for fences are usually the reverse: innermost fences are always (), next outer are [], etc. This means the opening fence has to wait until all the fences between it and the matching close have been detected before it can decide whether to be () or [] or {}.”

The fence level counting starts from innermost parentheses with one. For the next outer fences the level is increased by one. The example above with level indexes:

```
{_3a (_1b)_1 [_2c (_1d)_1]_2 (e)}_3
```

The correct level is only known at the closing symbol. Therefore the correct value is remembered in the main .aux file and used in the second L^AT_EX run.

1.1 User macros

```
\enparen {\langle text \rangle}
```

The macro `\enparen` puts its argument `\langle text \rangle` in parentheses. If the macro is nested, the used fence symbols change for the outer fences.

```
\enparenLeft
\enparenRight
```

Instead of `\enparen{text}` the left and right symbol can be used separately, but in pairs:

```
\enparenLeft text\enparenRight
```

`\enparenLeft` and `\enparenRight` may be used at different group levels, but they must be properly nested.

```
\enparenSetSymbols {\langle level \rangle} {\langle opening symbol \rangle} {\langle closing symbol \rangle}
```

Macro `\enparenSetSymbols` configures the `\langle opening symbol \rangle` and `\langle closing symbol \rangle` for the `\langle level \rangle`. The `\langle level \rangle` is a number and the counting starts with one. Level zero is used, if the correct level is not known (e.g. in the first L^AT_EX run). The package defines the following sets:

```
\enparenSetSymbols{0}{(){}}
\enparenSetSymbols{1}{(){}}
\enparenSetSymbols{2}{[]{}}
\enparenSetSymbols{3}{\{}{\}}
```

Example for changing the third and adding a fourth level:

```
\enparenSetSymbols{3}{\ensuremath{\langle}}{\ensuremath{\rangle}}
\enparenSetSymbols{4}{\{}{\}}
```

```
\enparenUnsetSymbols {\langle level \rangle}
```

The symbols for level $\langle level \rangle$ are removed. Example scenario: Only two nesting levels must be used, the package defines more, then the third level can be disabled by `\enparenUnsetSymbols{3}` and the user gets warnings if parentheses at level 3 are needed.

1.2 Contexts

```
\enparenBeginContext {\langle name \rangle}
\enparenEndContext {\langle name \rangle}
```

If the current text is interrupted by footnotes, floats with captions, then the parentheses inside the text of footnotes, captions, ... should restart from scratch. This can be achieved by embedding the text inside macros `\enparenBeginContext` and `\enparenEndContext`. These macros must be properly nested. The $\langle name \rangle$ for the begin and end macro must be the same. It is a help for debugging problems, because the warning messages show the context name. But it is not necessary that the begin/end pairs have different names. Example:

```
\enparenLeft text before table ...
\begin{table}
  \caption{Table caption}
  \enparenBegin{Context}{table}
  Other text \enparen{foobar}.
  \enparenEnd{Context}{table}
\end{table}
text after table ...
\enparenRight
```

The parentheses inside the table environment and context ‘table’ are not nested inside other parentheses: (foobar). In case of captions and footnotes the contexts are automatically added, see next section about options.

1.3 Options

```
\enparenSetup {\langle key value list \rangle}
```

Some options (currently all) can also be set after the package is loaded. They can be set in the argument $\langle key value list \rangle$ of `\enparenSetup`. Options are disabled after they are used the last time. Currently all options are boolean options and are disabled in `\begin{document}`.

caption: The caption text is put in a context `caption`.

footnote: The footnote text is put in a context `footnote`.

Example for disabling the two options at different places:

```
\usepackage[caption=false]{enparen}
\enparenSetup{footnote=false}
```

1.4 Notes

Implicit kerning: Unexpandable stuff might affect the implicit kerning. The package cannot avoid this, because it need to define and redefine macros at the occurrence of each symbol. This is done before the opening and after the closing symbol, thus that the implicit kerning inside is not affected.

2 Implementation

```
1 {*package}
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{enparen}
4 [2016/05/16 v1.1 Parentheses nesting (HO)]%
5 \RequirePackage{ltxcmds}[2011/11/09]
6 \ltx@IfUndefined{numexpr}{%
7   \PackageError{enparen}{%
8     Missing e-TeX's \ltx@backslashchar numexpr.\MessageBreak
9     The package will continue with emergency definitions%
10 }@\ehc
11 \def\enparenLeft{()%
12 \def\enparenRight{}%
13 \long\def\enparen#1{\enparenLeft#1\enparenRight}%
14 \let\enparenSetup\ltx@gobble
15 \let\enparenSetSymbols\ltx@gobblethree
16 \let\enparenUnsetSymbols\ltx@gobble
17 \endinput
18 }{%
19 \RequirePackage{protecteddef}[2011/01/31]
20 \RequirePackage{atveryend}[2011/06/30]
21 \RequirePackage{uniquecounter}[2011/01/30]
22 \RequirePackage{zref-base}[2011/03/18]
23 \RequirePackage{kvoptions}[2011/06/30]
24 \RequirePackage{kvsetkeys}[2011/10/18]
```

```
\zref@wrapper@mainaux
25 \providetcommand{\zref@wrapper@mainaux}[1]{%
26   \ifx\@auxout\@mainaux
27     #1%
28   \else
29     \begingroup
30     \let\@auxout\@mainaux
31     #1%
32     \endgroup
33   \fi
34 }
35 \UniqueCounterNew{enparen}
36 \zref@newprop{enparen}[0]{}
```

2.2 Contexts

```
\enparenContextDefault
37 \def\enparenContextDefault{main}

\enparen@ctx
38 \let\enparen@ctx\ltx@empty

\enparen@stack
39 \let\enparen@stack\ltx@empty
```

2.2.1 Stack for contexts

```
\enparen@CtxStack
40 \global\let\enparen@CtxStack\ltx@empty

\enparen@CtxStackPush
41 \def\enparen@CtxStackPush#1{%
42   \xdef\enparen@CtxStack{%
43     {\enparen@ctx}{\enparen@stack}%
44     \enparen@CtxStack
45   }%
46   \xdef\enparen@ctx{#1}%
47   \global\let\enparen@stack\ltx@empty
48 }

\enparen@CtxStackPop
49 \def\enparen@CtxStackPop{%
50   \ifx\enparen@CtxStack\ltx@empty
51     \PackageWarning{\enparen}{%
52       Pop request for empty context stack%
53     }%
54     \global\let\enparen@ctx\enparenContextDefault
55     \global\let\enparen@stack\ltx@empty
56   \else
57     \xdef\enparen@ctx{%
58       \expandafter\ltx@car\enparen@CtxStack@\nil
59     }%
60     \xdef\enparen@stack{%
61       \expandafter\ltx@carsecond\enparen@CtxStack@\nil
62     }%
63     \xdef\enparen@CtxStack{%
64       \expandafter\ltx@cdrtwo\enparen@CtxStack@\nil
65     }%
66   \fi
67 }
```

2.2.2 Context user macros

```
\enparenBeginContext
68 \ProtectedDef*{\enparenBeginContext}[1]{%
69   \enparen@CtxStackPush{#1}%
70 }

\enparenEndContext
71 \ProtectedDef*{\enparenEndContext}[1]{%
72   \edef\enparen@temp{#1}%
73   \ifx\enparen@temp\enparen@ctx
74   \else
75     \PackageWarning{\enparen}{%
76       Context mismatch in end request.\MessageBreak
77       '#1' should be ended, but current context\MessageBreak
78       is '\enparen@ctx'%
79     }%
80   \fi
81   \enparenCheckEmptyStack
82   \enparen@CtxStackPop
83 }

\enparenCheckEmptyStack
84 \ProtectedDef*{\enparenCheckEmptyStack}[0]{%
85   \ifx\enparen@stack\ltx@empty
86   \else
```

```

87      \PackageWarning{enparen}{%
88        Ending non-empty stack `\'enparen@ctx':\MessageBreak
89        \'enparen@PrintStack\MessageBreak
90      }%
91    \fi
92 }

```

```

\enparen@PrintStack
93 \def\enparen@PrintStack{%
94   \expandafter\enparen@PrintStackAux
95   \'enparen@stack\ltx@empty\ltx@empty
96 }

```

```

\enparen@PrintStackAux
97 \def\enparen@PrintStackAux#1#2{%
98   \ifx\ltx@empty#1%
99   \else
100     {#1:#2}%
101     \expandafter\enparen@PrintStackAux
102   \fi
103 }

```

2.3 Symbols

```

\enparenSetSymbols
104 \ProtectedDef*\{\enparenSetSymbols}[3]{%
105   \expandafter
106   \def\csname enparen@symbol\the\numexpr#1L\endcsname{#2}%
107   \expandafter
108   \def\csname enparen@symbol\the\numexpr#1R\endcsname{#3}%
109 }

```

```

\enparenUnsetSymbols
110 \ProtectedDef*\{\enparenUnsetSymbols}[1]{%
111   \expandafter
112   \let\csname enparen@symbol\the\numexpr#1L\endcsname\ltx@undefined
113   \expandafter
114   \let\csname enparen@symbol\the\numexpr#1R\endcsname\ltx@undefined
115 }

116 \enparenSetSymbols{0}{(){}}
117 \enparenSetSymbols{1}{(){}}
118 \enparenSetSymbols{2}{[]{}}
119 \enparenSetSymbols{3}{\{}{\}}
120 \enparenSetSymbols{4}{\ensuremath{\langle}}{\ensuremath{\rangle}}
```

2.4 Main user macros

```

\enparen
121 \ProtectedDef{\enparen}[1]{%
122   \enparenLeft#1\enparenRight
123 }

```

```

\enparenLeft
124 \ProtectedDef*\{\enparenLeft}[0]{%
125   \UniqueCounterCall{enparen}\enparen@Left
126 }

```

```

\enparen@Left
127 \def\enparen@Left#1{%
128   \xdef\enparen@stack{%

```

```

129      {#1}{1}%
130      \expandafter\enparen@Inc\expandafter2\expandafter!%
131      \enparen@stack\ltx@empty\ltx@empty
132  }%
133 \edef\enparen@tmp{\zref@extract{enparen#1}{enparen}}%
134 \ltx@ifundefined{enparen@symbol}\enparen@tmp L}{%
135     \PackageWarning{enparen}{%
136         Undefined symbols for level \enparen@tmp
137     }%
138     \csname enparen@symbol0L\endcsname
139 }{%
140     \csname enparen@symbol\enparen@tmp L\endcsname
141 }%
142 }

\enparen@Inc
143 \def\enparen@Inc#1#2#3{%
144     \ifx\ltx@empty#2%
145     \else
146         \ifnum#3<#1 %
147             {#2}{#1}%
148             \expandafter\enparen@Inc
149             \the\numexpr#1+1\expandafter\expandafter\expandafter!%
150         \else
151             {#2}{#3}%
152         \fi
153     \fi
154 }

\enparenRight
155 \ProtectedDef*\{\enparenRight}[0]{%
156     \ifx\enparen@stack\ltx@empty
157         \PackageWarning{enparen}{%
158             Missing left symbol for right symbol%
159         }%
160         \csname enparen@symbol0R\endcsname
161     \else
162         \expandafter\enparen@Right\enparen@stack\@nil
163     \fi
164 }

\enparen@Right
165 \def\enparen@Right#1#2#3\@nil{%
166     \ltx@ifundefined{%
167         enparen@symbol}%
168         \zref@extract{enparen#1}{enparen}}%
169     R%
170 }{%
171     \csname enparen@symbol0R\endcsname
172 }{%
173     \csname
174         enparen@symbol}%
175         \zref@extract{enparen#1}{enparen}}%
176     R%
177     \endcsname
178 }%
179 \zref@wrapper@mainaux{%
180     \zref@setcurrent{enparen}{#2}%
181     \zref@labelbyprops{enparen#1}{enparen}%
182 }%
183 \xdef\enparen@stack{#3}%
184 }

```

2.5 Options

```
185 \SetupKeyvalOptions{%
186   family=enparen,%
187   prefix=enparen@,%
188 }

\enparenSetup
189 \ProtectedDef*{\enparenSetup}[0]{%
190   \kvsetkeys{enparen}{%
191 }

192 \DeclareBoolOption[true]{footnote}
193 \DeclareBoolOption[true]{caption}
194 \ProcessKeyvalOptions*
```

2.6 Context settings

```
\enparen@AtBegin
195 \def\enparen@AtBegin{%
196   \ifenparen@footnote
197     \let\enparen@org@makefntext\@makefntext
198     \long\def\@makefntext##1{%
199       \enparen@org@makefntext{%
200         \enparenBeginContext{footnote}%
201         ##1%
202         \enparenEndContext{footnote}%
203       }%
204     }%
205   \fi
206   \enparen@Disable{footnote}%
207   \ifenparen@caption
208     \let\enparen@org@makecaption\@makecaption
209     \long\def\@makecaption##1##2{%
210       \enparen@org@makecaption{##1}{%
211         \enparenBeginContext{caption}%
212         ##2%
213         \enparenEndContext{caption}%
214       }%
215     }%
216   \fi
217   \enparen@Disable{caption}%
218 }

\enparen@Disable
219 \def\enparen@Disable#1{%
220   \DisableKeyvalOption[%
221     action=warning,%
222     package=enparen,%
223   ]{enparen}{#1}%
224 }

225 \AtBeginDocument{\enparen@AtBegin}
```

2.7 At end of document

```
\enparen@AtEnd
226 \def\enparen@AtEnd{%
227   \enparenCheckEmptyStack
228   \ifx\enparen@CtxStack\ltx@empty
229   \else
230     \PackageWarningNoLine{enparen}{%
231       Context stack is not empty at end of document.\MessageBreak
232 }
```

```

232      Current stack and contents of context stack:\MessageBreak
233      [\enparen@ctx]:[\enparen@PrintStack]%
234      \expandafter
235      \enparen@PrintContextStack\enparen@CtxStack\relax\relax
236      }%
237  \fi
238 }

\enparen@PrintContextStack
239 \def\enparen@PrintContextStack#1#2{%
240   \ifx\relax#1\ltx@empty
241   \else
242     \MessageBreak
243     [#1]:[\enparen@PrintStackAux#2\ltx@empty\ltx@empty]%
244     \expandafter\enparen@PrintContextStack
245   \fi
246 }

247 \AtVeryEndDocument{\enparen@AtEnd}
248 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/enparen.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/enparen.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex enparen.dtx
```

¹[CTAN:pkg/enparen](#)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
enparen.sty → tex/latex/oberdiek/enparen.sty  
enparen.pdf → doc/latex/oberdiek/enparen.pdf  
enparen.dtx → source/latex/oberdiek/enparen.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TeX` distribution (`TeX Live`, `MiKTeX`, ...) relies on file name databases, you must refresh these. For example, `TeX Live` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{enparen.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex enparen.dtx  
makeindex -s gind.ist enparen.idx  
pdflatex enparen.dtx  
makeindex -s gind.ist enparen.idx  
pdflatex enparen.dtx
```

4 References

- [1] Dan Luecking: *Re: bracket order*; newsgroup `comp.text.tex`; message id `<9b07c9c8-ff92-4cbf-b3a9-84efecfeb506@124g2000yqm.googlegroups.com>`
2012-01-05. <https://groups.google.com/group/comp.text.tex/msg/8774519da31c2352>

5 History

[2012/01/07 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	I
\@auxout	26, 30
\@ehc	10
\@mainaux	26, 30
\@makecaption	208, 209
\@makefntext	197, 198
\@nil	58, 61, 64, 162, 165
\{	119
\}	119
A	
\AtBeginDocument	225
\AtVeryEndDocument	247
C	
\csname	106, 108, 112, 114, 138, 140, 160, 171, 173
D	
\DeclareBoolOption	192, 193
\DisableKeyvalOption	220
E	
\endcsname	106, 108, 112, 114, 138, 140, 160, 171, 177
\endinput	17
\enparen	2, 13, <u>121</u>
\enparen@AtBegin	195, 225
\enparen@AtEnd	<u>226</u> , 247
\enparen@ctx <u>38</u> , 43, 46, 54, 57, 73, 78, 88, 233
\enparen@CtxStack	<u>40</u> , 42, 44, 50, 58, 61, 63, 64, 228, 235
\enparen@CtxStackPop	<u>49</u> , 82
\enparen@CtxStackPush	<u>41</u> , 69
\enparen@Disable	206, 217, <u>219</u>
\enparen@Inc	130, <u>143</u>
\enparen@Left	<u>125</u> , <u>127</u>
\enparen@org@makecaption	208, 210
\enparen@org@makefntext	197, 199
\enparen@PrintContextStack	<u>235</u> , <u>239</u>
\enparen@PrintStack	89, <u>93</u> , 233
\enparen@PrintStackAux	<u>94</u> , <u>97</u> , 243
\enparen@Right	162, <u>165</u>
\enparen@stack	<u>39</u> , 43, 47, 55, 60, 85, 95, 128, 131, 156, 162, 183
\enparen@temp	<u>72</u> , 73
\enparen@tmp	133, 134, 136, 140
\enparenBeginContext	3, <u>68</u> , 200, 211
\enparenCheckEmptyStack	81, <u>84</u> , 227
\enparenContextDefault	<u>37</u> , 54
\enparenEndContext	<u>71</u> , 202, 213
\enparenLeft	2, 11, 13, 122, <u>124</u>
\enparenRight	12, 13, 122, <u>155</u>
\enparenSetSymbols	2, 15, <u>104</u> , 116, 117, 118, 119, 120
\enparenSetup	3, 14, <u>189</u>
\enparenUnsetSymbols	3, 16, <u>110</u>
\ensuremath	120
I	
\ifenparen@caption	207
\ifenparen@footnote	196
\ifnum	146
\ifx	26, 50, <u>73</u> , 85, 98, 144, 156, 228, 240
K	
\kvsetkeys	190
L	
\langle	120
\ltx@backslashchar	8
\ltx@car	58
\ltx@carsecond	61
\ltx@cdrtwo	64
\ltx@empty	38, 39, 40, 47, 50, 55, 85, 95, 98, 131, 144, 156, 228, 240, 243
\ltx@gobble	14, 16
\ltx@gobblethree	15
\ltx@ifundefined	6, 134, 166
\ltx@undefined	112, 114
M	
\MessageBreak 8, 76, <u>77</u> , 88, 89, 231, 232, 242
N	
\NeedsTeXFormat	2
\numexpr	106, 108, 112, 114, 149
P	
\PackageError	7
\PackageWarning	51, <u>75</u> , 87, 135, 157
\PackageWarningNoLine	230
\ProcessKeyvalOptions	194
\ProtectedDef	68, 71, 84, 104, 110, 121, 124, 155, 189
\providecommand	25
\ProvidesPackage	3
R	
\range	120
\RequirePackage	5, 19, 20, 21, 22, 23, 24
S	
\SetupKeyvalOptions	185
T	
\the	106, 108, 112, 114, 149
U	
\UniqueCounterCall	125
\UniqueCounterNew	35
Z	
\zref@extract	133, 168, 175
\zref@labelbyprops	181
\zref@newprop	36
\zref@setcurrent	180
\zref@wrapper@mainaux	<u>25</u> , 179