

The `xfrac` package

Split-level fractions

The L^AT_EX Project*

Released 2024-06-04

The `xfrac` package defines a document command `\sfrac` with the following syntax:

```
\sfrac[<instance>]{<num>}[<sep>]{<denom>}
```

Let's show a few examples:

```
\sfrac{1}{2}, $\sfrac{1}{2}$,  
$\mathbf{3 \times \sfrac{1}{2}}$  
\quad \fontfamily{ppl}\selectfont Palatino: \sfrac{1}{2}  
\quad \fontfamily{ptm}\selectfont Times: \sfrac{1}{2}  
  
½, ½, 3 × ½    Palatino: ½    Times: ½
```

You'll notice something interesting: not only does the `\sfrac` command work as it should in math mode, it also gets the job done for other fonts as well.

1 A Bit of History

1.1 The Past

One of the first exercises in *The T_EXBook* is to design a macro for split level fractions. The solution presented is fairly simple, using a *virgule* (a slash) for separating the two components. It looks okay because the text font and math font of Computer Modern look almost identical.

The proper symbol to use instead of the virgule is a *solidus* which does not exist in Computer Modern. It is however available in the European Computer Modern fonts, but I'll get back to that.

1.2 The Present

The most common way to produce split level fractions within L^AT_EX 2 _{ε} is by means of the `nicefrac` package. Part of the reason it has found widespread use is due to the strange design of the built-in text fractions of the EC fonts, which look like this: ½. The package is very simple to use but there are a few issues:

- It uses the virgule instead of the solidus.

*E-mail: latex-team@latex-project.org

- Font size of numerator and denominator is bigger than in the built-in symbol. Compare Palatino: \textonehalf vs. $\frac{1}{2}$.
- It doesn't correct for fonts using text figures such as in the `ecofont` package. Compare \textonehalf and $\text{\textfrac{8}{9}}$.
- In math mode, it doesn't always pick up the correct math alphabet.

In short: `nicefrac` doesn't attempt to be the answer to everything and so this is not a criticism of the package. It works quite well for Computer Modern which was pretty much what was widely available at the time it was developed. Users these days, however, have a choice of many fonts when they write their documents.

1.3 The Future

Fonts are wildly different; one macro that works fine for Computer Modern obviously doesn't work well at all in Palatino. For one we have to make the separator symbol configurable, and we need to take care of several details as well: font scaling of the numerator/denominator pair (ND), font selection of ND, *etc.* If we are to have a single package for this in the future we have to define a totally generic interface for the fraction commands and then adjust parameters depending on the current font. What you see in this prototype implementation of `xfrac` is just that.

2 Advanced User Interface

2.1 Text mode

The usual problem in text mode has a name: Computer Modern. The solidi of all the Computer Modern fonts leave a lot to be desired, although things are potentially looking better as the Latin Modern fonts are becoming more stable and widespread. As long as the default fonts are Computer Modern variants we must however work around this. One idea that comes to mind is to see what happens when you use a solidus from another font instead. Let's try with Times:

“You take \textonehalf cup of sugar, . . .”

That looks quite good actually, so it was probably very difficult to obtain that result. Nope, it was extremely easy—if you happen to know about *instances*:

```
\DeclareInstance{xfrac}{cmr}{text}
  {slash-symbol-font = ptm}
```

So we define an instance with the name `cmr` from the template `text` which in turn is of object type `xfrac`. You'll notice the `cmr` is also the name of the font family for Computer Modern Roman and the reasoning behind is that every font family should have its own settings, and if a document command is to work well in that scheme, letting it use the name of the current font family seems like a good idea. Thus the `\sfrac` command checks to see whether an instance with same name as the current font family exists and uses it if the test is true; otherwise the default setting is used. Here we defined the instance to be used for the font family `cmr` and just told it to use the Times font for typesetting the slash symbol which turns out to be a solidus by default.

The option `cm-recommended` which is loaded by default uses the Times solidus for Computer Modern Roman and Computer Modern Sans Serif and the Palatino solidus for Computer Modern Typewriter Type. This looks quite good. Should you however not want this you can use the option `cm-standard` which produces somewhat acceptable results using Computer Modern exclusively.

So what about old style figures? If you use the `eco` package you might define an instance similar to this ('`cmor`' is the name of the roman font activated by `eco`):

```
\DeclareInstance{xfrac}{cmor}{text}
{
    slash-symbol-font = ptm,
    numerator-font    = cmr,
    denominator-font  = cmr
}
```

We also use regular Computer Modern Roman for typesetting ND, so we end up with $\frac{1}{2}$ and $\frac{8}{9}$ instead of $\frac{1}{2}$ and $\frac{8}{9}$. Much better.

There are also situations where other tricks are useful. If you don't have the inferior and superior figures available in a font, or the font doesn't have a wider design for small font sizes, you can cheat by manually scaling the ND-pair. I got nice results for Adobe's Stempel Garamond (with small caps and old style figures) with the following setup:

```
\DeclareInstance{xfrac}{pegj}{text}
{
    numerator-font    = pegx,
    denominator-font = pegx,
    scale-factor      = 0.9,
    h-scale           = 1.1
}
```

We use the font family `pegx` (Stempel Garamond with real small caps) for typesetting the ND-pair. Additionally the key `scale-factor` specifies that the font size used for the ND-pair should be 0.9 of the height of the solidus, and the key `h-scale` specifies that the ND-pair should be scaled an extra 10 % horizontally.

Should you be so fortunate the have a font with inferior and superior figures like in the Monotype Janson example from Philipp Lehman's excellent *The Font Installation Guide*. In that example Philipp defines the font families `mjn0` for the inferior figures and `mjn1` for the superior. Thus to get the `\sfrac` command to use them on the fly for the font family `mjnj` (Janson, old style figures) we would say

```
\DeclareInstance{xfrac}{mjnj}{text}
{
    numerator-font    = mjn1,
    denominator-font = mjn0,
    scaling           = false,
    numerator-bot-sep = 0 pt,
    denominator-bot-sep = 0 pt
}
```

I think this example is a very clean way to do it. An alternative approach could be to use the keys `numerator-format` and `denominator-format` to process the arguments and let them determine what to do.

2.2 Math Mode

In math mode the choices are a lot fewer because first of all TeX comes with a built-in limitation of 16 math families. Additionally we will not need a solidus for typesetting split fractions in math, as tradition is to use a virgule instead. We define the basic `mathdefault` instance to simply use the math family in use when the instance is run. So if we're in normal math like `\sfrac{7}{9}` we simply get family -1. If we're inside a `\mathbf` we're in family 4 (in the standard setup at least), and so the fraction is typeset with the same math family. Simple, isn't?

You can also declare instances for the math families, but I really don't see why you would. If you do then name them according to the scheme `mathfam<N>`, where `<N>` is the family number, and only do it if you *really* know how to set up math fonts. That is, if `\DeclareMathAlphabet` is unbeknownst to you, then just don't go there.

3 The Template Interface

3.1 The object type ‘xfrac’

Arg: 1 The numerator

Arg: 2 The separator

Arg: 3 The denominator

Semantics:

Typesets arguments 1 and 3 separated by argument 2, which in text mode by default is a *solidus*. This is taken from `textcomp` where it is denoted `\textfractionsolidus`. This is the character used for the ready made split level fractions such as $\frac{1}{2}$ —except in the (European) Computer Modern fonts. In math mode a *virgule* is used instead as this is more appropriate and it is always available in the math fonts. The solidus is a text symbol only.

3.2 The template ‘text’ (object type xfrac)

Attributes:

numerator-font (tokenlist) Font family specification to use for the numerator.
Default: `\f@family`

numerator-format (function 1 arg) Action to be taken on the numerator.
Default: Process argument unchanged

slash-symbol (tokenlist) The separator symbol. If not specified the default value will be used instead.
Default: Solidus (`\textfractionsolidus`)

slash-symbol-font (tokenlist) Font family specification to use for the separator symbol.
Default: `\f@family`

slash-symbol-format (function 1 arg) Action to be taken on the separator symbol.
Default: Process argument unchanged

denominator-font (tokenlist) Font family specification to use for the denominator.
Default: \f@family

denominator-format (function 1 arg) Action to be taken on the denominator.
Default: Process argument unchanged

h-scale (real) Factor by which the numerator and denominator should be horizontally scaled. It should only be used if the real superior and inferior fonts are not available. For instance Stempel Garamond looks excellent if scaled 10% extra horizontally, *i.e.*, by a factor of 1.1. Default: 1

v-scale (real) Same as **h-scale** only vertically. Probably not of much use but added for completeness. Default: 1

scale-factor (real) Fraction of the size of **slash-symbol**. Used for setting the font size of numerator and denominator. Usually a value of app. $\frac{5}{6}$ produces fine results. It should only be used if the real superior and inferior fonts are not available. As an example Stempel Garamond looks better if the factor is 0.9. Default: 0.83333

scale-relative (choice) If set to **true** the font size of the numerator and denominator is scaled with respect to the height of the **slash-symbol**. If set to **false** the font is scaled with respect to the total height of the **slash-symbol**. Default: true

scaling (choice) If set to **true** the fonts are allowed to scale. If set to **false** they are not. See the ‘Janson’ example for an application. Default: true

numerator-top-sep (length) Dimension specifying the space between the top of the **slash-symbol** and the top of the numerator. If not specified, the depth of the solidus will be used, because this value will make the fraction look even.
Default: Unspecified

numerator-bot-sep (length) Dimension specifying the lift of the numerator from the baseline. Default: Unspecified

denominator-bot-sep (length) Dimension specifying the lift of the denominator from the baseline. Default: Unspecified

slash-right-kern (length) Dimension specifying the kerning between the **slash-symbol** and the numerator. Default: 0pt

slash-left-kern (length) Dimension specifying the kerning between the **slash-symbol** and the denominator. Default: 0pt

math-mode (choice) Are we in math mode or not? Default: false

phantom (tokenlist) A character that suits the common cases. As we would mostly want to use numbers in text mode we choose a “tall” number, while in math it is somewhat different. Default: 8

Semantics & Comments:

This template is also the foundation for the “math” template. The keys **slash-right-mkern** and **slash-left-mkern** can only be used in math mode and are not shown here.

3.3 The template ‘math’ (object type xfrac)

Attributes:

numerator-font (tokenlist)	Font family specification to use for the numerator.	Default: \number\fam
slash-symbol (tokenlist)	The separator symbol. If not specified the default value will be used instead.	Default: Virgule (/)
slash-symbol-font (tokenlist)	Font family specification to use for the separator symbol.	Default: \number\fam
denominator-font (tokenlist)	Font family specification to use for the denominator.	Default: \number\fam
scale-factor (real)	Fraction of the size of slash-symbol . In math mode we cannot rely on the fonts to be able to scale, but giving a default scale of 0.7 fits into the regular size changing scheme—the default scheme has values $(D, T, S, SS) = (1, 1, 0.7, 0.5)$ whereas we with a default scale-factor of 0.7 get $(1, 1, 0.7, 0.49)$. That’s close enough.	Default: 0.7
scale-relative (choice)	If set to true the font size of the numerator and denominator is scaled with respect to the height of the slash-symbol . If set to false the font is scaled with respect to the total height of the slash-symbol .	Default: false
scaling (choice)	If set to true the fonts are allowed to scale. If set to false they are not. See the plainmath example for an application.	Default: true
numerator-top-sep (length)	Dimension specifying the space between the top of the slash-symbol and the top of the numerator. If not specified, the depth of the virgule will be used, because this value will make the fraction look even.	Default: Opt
denominator-bot-sep (length)	Dimension specifying the lift of the denominator from the baseline.	Default: Opt
slash-right-mkern (muskip)	Same as slash-right-kern but for math mode only and should be specified in mu units.	Default: -2mu
slash-left-mkern (muskip)	Same as slash-left-kern but for math mode only and should be specified in mu units.	Default: -1mu
math-mode (choice)	Are we in math mode or not?	Default: true
phantom (tokenlist)	A character that suits the common cases. In math we have a high risk of using a parenthesis, so we choose that. Text mode is another story.	Default: (

Semantics & Comments:

This template is a restricted version of the **text** template. Only the keys that are different from the **text** template are shown here. Also bear in mind that the attributes **slash-left-kern** and **slash-right-kern** have no meaning in this template.

4 xfrac implementation

```
1  {*package}
2  {@@=xfrac}

    Load expl3 “up-front” only if required.
3  \Qifundefined{ExplLoaderFileDate}
4      {\RequirePackage{expl3}}
5  {}

Make sure that the version of l3kernel in use is sufficiently new. We use \ExplFileVersion as \Qifpackagelater doesn’t work for pre-loaded expl3 in the absence of the package.
```

```
6  \Qifl@t@r\ExplLoaderFileVersion{2018-02-21}
7  {}
8  {%
9      \PackageError{xfrac}{Support package expl3 too old}
10     {%
11         You need to update your installation of 'l3kernel'.\MessageBreak
12         Loading-xfrac-will-abort!%
13     }%
14     \endinput
15   }%
16 \ProvidesExplPackage{xfrac}{2024-06-04}{}%
17   {Split-level fractions}
```

\IfFormatAtLeastTF Not present in older kernels: use the L^AT_EX 2_E mechanism as this is correct for this case.

```
18 \providecommand \IfFormatAtLeastTF { \Qifl@t@r \fmtversion }
```

(End of definition for \IfFormatAtLeastTF. This function is documented on page ??.)

```
19 \IfFormatAtLeastTF { 2020-02-02 }
20 {
21   { \RequirePackage { textcomp } }
22 \IfFormatAtLeastTF { 2020-10-01 }
23 {
24   { \RequirePackage { xparse } }
```

\l_xfrac_cm_std_bool There is one option to support.

```
25 \keys_define:nn { xfrac }
26 {
27   cm-recommended .choice:,
28   cm-recommended /
29   false .code:n =
30   { \bool_set_true:N \l_xfrac_cm_std_bool },
31   cm-recommended /
32   true .code:n =
33   { \bool_set_false:N \l_xfrac_cm_std_bool },
34   cm-recommended .default:n = { true },
35   cm-standard .bool_set:N = \l_xfrac_cm_std_bool
36 }
```

(End of definition for \l_xfrac_cm_std_bool.)

```
37 \IfFormatAtLeastTF { 2022-06-01 }
38   { \ProcessKeyOptions }
```

```

39  {
40    \RequirePackage { 13keys2e }
41    \ProcessKeysOptions { xfrac }
42  }
43 \IfFormatAtLeastTF { 2024-06-01 }
44  {
45    { \RequirePackage { xtemplate } }
46 \cs_if_exist:NF \IfInstanceExistsTF
47  { \cs_new_eq:NN \IfInstanceExistsTF \IfInstanceExistTF }

```

`\l_xfrac_slash_box` In keeping with the L^AT_EX3 philosophy, rather than use generic scratch boxes and get confused, `xfrac` reserves its own named working space.

```

48 \box_new:N \l_xfrac_slash_box
49 \box_new:N \l_xfrac_tmp_box

```

(*End of definition for \l_xfrac_slash_box and \l_xfrac_tmp_box.*)

`_xfrac_tmp:w` Used for the raised boxes: weird as it does not take an argument but the `\raisebox` does.

```
50 \cs_new:Npn \_xfrac_tmp:w { }
```

(*End of definition for _xfrac_tmp:w.*)

4.1 Initialisation of variables

Variables used in templates have to be set up: there is not much to say about these, other than that they must exist.

Fixed lengths.

```

51 \dim_new:N \l_xfrac_denominator_bot_sep_dim
52 \dim_new:N \l_xfrac_numerator_bot_sep_dim
53 \dim_new:N \l_xfrac_numerator_top_sep_dim
54 \dim_new:N \l_xfrac_slash_left_sep_dim
55 \dim_new:N \l_xfrac_slash_right_sep_dim

```

(*End of definition for \l_xfrac_denominator_bot_sep_dim and others.*)

Math mode skips.

```

56 \muskip_new:N \l_xfrac_slash_left_muskip
57 \muskip_new:N \l_xfrac_slash_right_muskip

```

(*End of definition for \l_xfrac_slash_left_muskip and \l_xfrac_slash_right_muskip.*)

Floating point values.

```

58 \fp_new:N \l_xfrac_hscale_fp
59 \fp_new:N \l_xfrac_scale_factor_fp
60 \fp_new:N \l_xfrac_vscale_fp

```

(*End of definition for \l_xfrac_hscale_fp, \l_xfrac_scale_factor_fp, and \l_xfrac_vscale_fp.*)

Token lists, which include floating-point numbers and math(s) skips.

```

61 \tl_new:N \l_xfrac_denominator_font_tl
62 \tl_new:N \l_xfrac_numerator_font_tl
63 \tl_new:N \l_xfrac_phantom_tl
64 \tl_new:N \l_xfrac_slash_symbol_tl
65 \tl_new:N \l_xfrac_slash_symbol_font_tl

```

(End of definition for `\l_xfrac_denominator_font_t1` and others.)

Functions, either things which are calculated “on the fly” (no argument required) or are functions taking one argument in the code.

```
66 \cs_new:Npn \__xfrac_fontscales: { }
67 \cs_new:Npn \__xfrac_math:n #1 { }
68 \cs_new:Npn \__xfrac_denominator_change: { }
69 \cs_new:Npn \__xfrac_denominator_format:n #1 { }
70 \cs_new:Npn \__xfrac_numerator_change: { }
71 \cs_new:Npn \__xfrac_numerator_format:n #1 { }
72 \cs_new:Npn \__xfrac_relscale: { }
73 \cs_new:Npn \__xfrac_slash_symbol_change: { }
74 \cs_new:Npn \__xfrac_slash_symbol_format:n #1 { }
75 \cs_new:Npn \__xfrac_text_or_math:n #1 { }
```

(End of definition for `__xfrac_fontscales:` and others.)

4.2 The template

There is only one object type in `xfrac`, rather unimaginatively named `xfrac`.

```
76 \IfFormatAtLeastTF { 2024-06-01 }
77   { \NewTemplateType }
78   { \DeclareObjectType }
79     { xfrac } { 3 }
```

A single template interface is used for both text and math(s), which does make a few things a little complex later.

```
80 \DeclareTemplateInterface { xfrac } { text } { 3 }
81   {
82     denominator-bot-sep : length      = \c_max_dim          ,
83     denominator-font    : tokenlist   = \f@family           ,
84     denominator-format  : function 1 = #1                  ,
85     h-scale             : real       = 1                  ,
86     math-mode           : choice { false , true }          =
87                               false                ,
88     numerator-font     : tokenlist   = \f@family           ,
89     numerator-format   : function 1 = #1                  ,
90     numerator-bot-sep : length      = \c_max_dim          ,
91     numerator-top-sep : length      = \c_max_dim          ,
92     phantom            : tokenlist   = 8                  ,
93     scale-factor       : real       = 0.83333           ,
94     scale-relative     : choice { false , true }          =
95                               true                ,
96     scaling            : choice { false , true }          =
97                               true                ,
98     slash-left-kern   : length      = 0 pt               ,
99     slash-left-mkern  : muskip     = -2 mu              ,
100    slash-right-kern  : length      = 0 pt               ,
101    slash-right-mkern : muskip     = -1 mu              ,
102    slash-symbol      : tokenlist   = \textfractionsolidus ,
103    slash-symbol-font : tokenlist   = \f@family           ,
104    slash-symbol-format: function 1 = #1                  ,
105    v-scale            : real       = 1                  ,
```

Most of the variable binding is quite simple: of course, the choices are a little more complicated. That is particularly true where these have to set up “on the fly” functions.

```

107 \DeclareTemplateCode { xfrac } { text } { 3 }
108 {
109   denominator-bot-sep = \l_xfrac_denominator_bot_sep_dim ,
110   denominator-font    = \l_xfrac_denominator_font_tl      ,
111   denominator-format  = \_xfrac_denominator_format:n       ,
112   h-scale             = \l_xfrac_hscale_fp                 ,
113   math-mode            =
114   {
115     false = \cs_set_eq:NN \_xfrac_math:n \use:n,
116     true  = \cs_set_eq:NN \_xfrac_math:n \ensuremath
117   },
118   numerator-font      = \l_xfrac_numerator_font_tl      ,
119   numerator-format    = \_xfrac_numerator_format:n       ,
120   numerator-bot-sep  = \l_xfrac_numerator_bot_sep_dim   ,
121   numerator-top-sep  = \l_xfrac_numerator_top_sep_dim   ,
122   phantom              = \l_xfrac_phantom_tl           ,
123   scale-factor         = \l_xfrac_scale_factor_fp       ,
124   scale-relative        =
125   {
126     false =
127       \cs_set:Npn \_xfrac_relscale:
128       {
129         \dim_eval:n
130         { \box_ht:N \l_xfrac_tmp_box + \box_dp:N \l_xfrac_tmp_box }
131       },
132     true  =
133       \cs_set:Npn \_xfrac_relscale:
134       { \dim_eval:n { \box_ht:N \l_xfrac_slash_box } }
135   },
136   scaling              =
137   {
138     false = \cs_set_eq:NN \_xfrac_fontscales: \prg_do_nothing:,
139     true  =
140       \cs_set:Npn \_xfrac_fontscales:
141       {
142         \fontsize
143         { \fp_to_dim:n { \l_xfrac_scale_factor_fp * \_xfrac_relscale: } }
144         { \c_zero_dim }
145         \selectfont
146       }
147   },
148   slash-left-kern      = \l_xfrac_slash_left_sep_dim      ,
149   slash-left-mkern     = \l_xfrac_slash_left_muskip      ,
150   slash-right-kern    = \l_xfrac_slash_right_sep_dim     ,
151   slash-right-mkern   = \l_xfrac_slash_right_muskip     ,
152   slash-symbol         = \l_xfrac_slash_symbol_tl       ,
153   slash-symbol-font   = \l_xfrac_slash_symbol_font_tl   ,
154   slash-symbol-format = \_xfrac_slash_symbol_format:n    ,
155   v-scale              = \l_xfrac_vscale_fp
156 }
```

The implementation part starts with applying all of the settings from above. The first

part of the set up is then to determine whether the surroundings are text or math(s), and react accordingly.

```

157  {
158  \mode_if_math:TF
159  {
160      \cs_set_eq:NN \__xfrac_text_or_math:n \text
161      \cs_set:Npe \__xfrac_denominator_font_change:
162          { \tex_fam:D \l__xfrac_denominator_font_tl }
163      \cs_set:Npe \__xfrac_numerator_font_change:
164          { \tex_fam:D \l__xfrac_numerator_font_tl }
165      \cs_set:Npe \__xfrac_slash_symbol_font_change:
166          { \tex_fam:D \l__xfrac_slash_symbol_font_tl }
167  }
168  {
169      \cs_set_eq:NN \__xfrac_text_or_math:n \mbox
170      \cs_set:Npn \__xfrac_denominator_font_change:
171          {
172              \fontfamily { \l__xfrac_denominator_font_tl }
173              \selectfont
174          }
175      \cs_set:Npn \__xfrac_numerator_font_change:
176          {
177              \fontfamily { \l__xfrac_numerator_font_tl }
178              \selectfont
179          }
180      \cs_set:Npn \__xfrac_slash_symbol_font_change:
181          {
182              \fontfamily { \l__xfrac_slash_symbol_font_tl }
183              \selectfont
184          }
185  }

```

Everything is now either inside `\text` or an `\mbox`, depending upon the surroundings. First, there are some boxes to set up.

```

186  \__xfrac_text_or_math:n
187  {
188      \m@th
189      \hbox_set:Nn \l__xfrac_tmp_box
190          { \__xfrac_math:n { \vphantom { ( ) } } }
191      \hbox_set:Nn \l__xfrac_slash_box
192          {
193              \__xfrac_math:n
194                  {
195                      \__xfrac_slash_symbol_format:n
196                          {
197                              \__xfrac_math:n
198                                  {
199                                      \__xfrac_slash_symbol_font_change:
200                                      \IfNoValueTF {#2}
201                                          { \l__xfrac_slash_symbol_tl } {#2}
202                                  }
203                          }
204                  }
205  }

```

Check on the numerator separator dimensions. The code starts with the assumption that neither has been given, as this can then be used to set up a default, which is also used when both values are set erroneously.

```

206   \cs_set:Npn \__xfrac_tmp:w
207   {
208     \raisebox
209     {
210       \dim_eval:n
211       {
212         \box_ht:N \l__xfrac_slash_box
213         - \box_dp:N \l__xfrac_slash_box
214         - \height
215       }
216     }
217   }
218 \dim_compare:nNnTF
219 { \l__xfrac_numerator_top_sep_dim } = { \c_max_dim }
220 {
221   \dim_compare:nNnf
222   { \l__xfrac_numerator_bot_sep_dim } = { \c_max_dim }
223   {
224     \cs_set:Npn \__xfrac_tmp:w
225     {
226       \raisebox
227       { \dim_use:N \l__xfrac_numerator_bot_sep_dim }
228     }
229   }
230 }
231 {
232   \dim_compare:nNnTF
233   { \l__xfrac_numerator_bot_sep_dim } = { \c_max_dim }
234   {
235     \cs_set:Npn \__xfrac_tmp:w
236     {
237       \raisebox
238       {
239         \dim_eval:n
240         {
241           \box_ht:N \l__xfrac_slash_box
242           - \dim_use:N \l__xfrac_numerator_top_sep_dim
243           - \height
244         }
245       }
246     }
247   }
248   {
249     \msg_error:nn { xfrac }
250     { over-specified-numerator-sep }
251   }
252 }
```

Typeset the numerator.

```

253   \__xfrac_tmp:w
254   {
```

```

255     \__xfrac_fontscales:
256     \__xfrac_numerator_format:n
257     {
258         \scalebox
259             { \fp_use:N \l__xfrac_hscale_fp }
260             [ \fp_use:N \l__xfrac_vscale_fp ]
261             {
262                 \__xfrac_math:n
263                 {
264                     \__xfrac_numerator_font_change:
265                     {
266                         \vphantom { \l__xfrac_phantom_tl }
267                         #1
268                     }
269                 }
270             }
271         }
272     }
273 \__xfrac_math:n
274 { % THIS IS JUST WRONG!
275     \mode_if_math:TF
276         { \tex_mskip:D \l__xfrac_slash_right_muskip }
277         { \tex_hskip:D \l__xfrac_slash_right_sep_dim }
278     }

```

Typeset the separator.

```

279     \box_use:N \l__xfrac_slash_box
280     \__xfrac_math:n
281     {
282         \mode_if_math:TF
283             { \tex_mskip:D \l__xfrac_slash_left_muskip }
284             { \tex_hskip:D \l__xfrac_slash_left_sep_dim }
285     }

```

Typeset the denominator.

```

286     \dim_compare:nNnTF
287         { \l__xfrac_denominator_bot_sep_dim } = { \c_max_dim }
288         {
289             \cs_set:Npn \__xfrac_tmp:w
290                 { \raisebox { - \box_dp:N \l__xfrac_slash_box } }
291         }
292         {
293             \cs_set:Npn \__xfrac_tmp:w
294                 {
295                     \raisebox
296                         { \dim_use:N \l__xfrac_denominator_bot_sep_dim }
297                 }
298         }
299     \__xfrac_tmp:w
300     {
301         \__xfrac_fontscales:
302         \__xfrac_denominator_format:n
303         {
304             \scalebox
305                 { \fp_use:N \l__xfrac_hscale_fp }

```

```

306      [ \fp_use:N \l_xfrac_vscaled_fp ]
307      {
308          \_xfrac_math:n
309          {
310              \_xfrac_denominator_font_change:
311              {
312                  \vphantom { \l_xfrac_phantom_t1 }
313                  #3
314              }
315          }
316      }
317  }
318 }
319 }
320 }

```

Since `math(s)` and `text` mode are wildly different entities we define a separate template for each. You already saw the “`text`” template, and here is the “`math`” template.

```

321 \IfFormatAtLeastTF { 2024-06-01 }
322 {
323     \DeclareTemplateCopy { xfrac } { math } { text }
324     \EditTemplateDefaults { xfrac } { math }
325 }
326 { \DeclareRestrictedTemplate { xfrac } { text } { math } }
327 {
328     numerator-font      = \number \fam ,
329     slash-symbol         = / ,
330     slash-symbol-font   = \number \fam ,
331     denominator-font    = \number \fam ,
332     scale-factor        = 0.7 ,
333     scale-relative       = false ,
334     scaling              = true ,
335     denominator-bot-sep = 0 pt ,
336     math-mode            = true ,
337     phantom              = ( % )
338 }

```

4.3 The standard instances

For the default instances we just use the relevant templates with the default settings.

The default “`text`” instance.

```
339 \DeclareInstance { xfrac } { default } { text } { }
```

The default “`math(s)`” instance. We cannot set the `numerator-top-sep` in the restricted template above.

```

340 \DeclareInstance { xfrac } { mathdefault } { math }
341 { numerator-top-sep = Opt }
```

Default Computer Modern setup. Far from optimal, but better than nothing.

```

342 \DeclareInstance { xfrac } { cmr } { text }
343 {
344     denominator-bot-sep = 0 pt ,
345     numerator-top-sep   = 0.2 ex ,
346     slash-left-kern     = -0.1 em ,
```

```

347     slash-right-kern    = -0.1 em
348 }
349 \DeclareInstance { xfrac } { cmss } { text }
350 {
351     denominator-bot-sep = 0 pt    ,
352     numerator-top-sep   = 0.2 ex  ,
353     slash-left-kern    = -0.1 em ,
354     slash-right-kern   = -0.1 em
355 }
356 \DeclareInstance { xfrac } { cmtt } { text }
357 {
358     denominator-bot-sep = 0 pt    ,
359     numerator-top-sep   = 0.2 ex  ,
360     slash-left-kern    = -0.1 em ,
361     slash-right-kern   = -0.1 em
362 }

```

We can do better for the Computer Modern fonts. For cmr and cmss we choose Times, and for cmtt use Palatino.

```

363 \bool_if:NF \l__xfrac_cm_std_bool
364 {
365     \DeclareInstance { xfrac } { cmr } { text }
366     { slash-symbol-font = ptm }
367     \DeclareInstance { xfrac } { cmss } { text }
368     { slash-symbol-font = ptm }
369     \DeclareInstance { xfrac } { cmtt } { text }
370     { slash-symbol-font = ppl }
371 }

```

Things works slightly better with Latin Modern.

```

372 \DeclareInstance { xfrac } { lmr } { text }
373 {
374     denominator-bot-sep = 0 pt    ,
375     numerator-top-sep   = 0.1 ex  ,
376     slash-left-kern    = -0.15 em ,
377     slash-right-kern   = -0.15 em
378 }
379 \DeclareInstance { xfrac } { lmss } { text }
380 {
381     denominator-bot-sep = 0 pt    ,
382     numerator-top-sep   = 0 pt    ,
383     slash-left-kern    = -0.15 em ,
384     slash-right-kern   = -0.15 em
385 }
386 \DeclareInstance { xfrac } { lmtt } { text }
387 {
388     denominator-bot-sep = 0 pt    ,
389     numerator-top-sep   = 0 pt    ,
390     slash-left-kern    = -0.15 em ,
391     slash-right-kern   = -0.15 em
392 }

```

4.4 The user command

`\sfrac` Currently there is just a single user command. `\sfrac` takes two mandatory arguments: numerator and denominator. It can take an optional argument between the mandatory specifying the separator like this:

$$\frac{7}{12}$$

It also has an optional argument that comes before the first mandatory argument. If used it will use that instance instead of the auto-detected one, so a user who has defined the instance “cmr2” may use

\sfrac [cmr2] {7}{12}

and get the settings from “cmr2” instead of the settings of the current font family.

```

393 \NewDocumentCommand \sfrac { o m o m }
394 {
395     \mode_if_math:TF
396     {
397         \IfInstanceExistsTF { xfrac } { mathfam \number \fam }
398         { \UseInstance { xfrac } { mathfam \number \fam } }
399         { \UseInstance { xfrac } { mathdefault } }
400         {#2} {#3} {#4}
401     }
402     {
403         \IfInstanceExistsTF { xfrac } {#1}
404         { \UseInstance { xfrac } {#1} }
405         {
406             \IfInstanceExistsTF { xfrac } { \f@family }
407             { \UseInstance { xfrac } { \f@family } }
408             { \UseInstance { xfrac } { default } }
409             {}
410             {#2} {#3} {#4}
411         }
412     }
413 }

```

(End of definition for \sfrac. This function is documented on page ???.)

4.5 Messages

Just the one.

```
413 \msg_new:nnn { xfrac } { over-specified-numerator-sep }
414   { You~have~specified~both~"numerator-top-sep"~and~"numerator-bot-sep". }
415   { I~will~pretend~that~you~didn't~specify~either~of~them. }
416 </package>
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

B

bool commands:

\bool_set_false:N	33	H	
\bool_set_true:N	30	hbox commands:	
box commands:		\hbox_set:Nn	189, 191
\box_dp:N	130, 213, 290	\height	214, 243
\box_ht:N	130, 134, 212, 241	I	
\box_new:N	48, 49	\IfFormatAtLeastTF	18, 19, 22, 37, 43, 76, 321
\box_use:N	279	\IfInstanceExistsTF	46, 47, 397, 403, 406
C		\IfInstanceExistTF	47
cs commands:		\IfNoValueTF	200
\cs_if_exist:NTF	46	K	
\cs_new:Npn	50,	keys commands:	
66, 67, 68, 69, 70, 71, 72, 73, 74, 75		\keys_define:nn	25
\cs_new_eq:NN	47	M	
\cs_set:Npe	161, 163, 165	\mathbf	4
\cs_set:Npn	127, 133, 140,	\mbox	11, 169
170, 175, 180, 206, 224, 235, 289, 293		\MessageBreak	11
\cs_set_eq:NN	115, 116, 138, 160, 169	mode commands:	
D		\mode_if_math:TF	158, 275, 282, 395
\DeclareInstance	339, 340, 342,	msg commands:	
349, 356, 365, 367, 369, 372, 379, 386		\msg_error:nn	249
\DeclareMathAlphabet	4	\msg_new:nnnn	413
\DeclareObjectType	78	muskip commands:	
\DeclareRestrictedTemplate	326	\muskip_new:N	56, 57
\DeclareTemplateCode	107	N	
\DeclareTemplateCopy	323	>NewDocumentCommand	393
\DeclareTemplateInterface	80	>NewTemplateType	77
dim commands:		\number	6, 328, 330, 331, 397, 398
\dim_compare:nNnTF	218, 221, 232, 286	P	
\dim_eval:n	129, 134, 210, 239	\PackageError	9
\dim_new:N	51, 52, 53, 54, 55	prg commands:	
\dim_use:N	227, 242, 296	\prg_do_nothing:	138
\c_max_dim	82, 90, 91, 219, 222, 233, 287	\ProcessKeyOptions	38
\c_zero_dim	144	\ProcessKeysOptions	41
E		\providecommand	18
>EditTemplateDefaults	324	\ProvidesExplPackage	16
\endinput	14	R	
\ensuremath	116	\raisebox	8, 208, 226, 237, 290, 295
\ExplFileVersion	7	\RequirePackage	4, 21, 24, 40, 45
\ExplLoaderFileVersion	6	S	
F		\scalebox	258, 304
\fam	6, 328, 330, 331, 397, 398	\selectfont	145, 173, 178, 183
\fmtversion	18	\sfrac	1–3, 16, 393
\fontfamily	172, 177, 182	T	
\fontsize	142	TeX and L ^A T _E X 2 _{&} commands:	
fp commands:		\@ifl@t@r	6, 18
\fp_new:N	58, 59, 60	\@ifpackagelater	7
\fp_to_dim:n	143		
\fp_use:N	259, 260, 305, 306		

```

\@ifundefined ..... 3
\f@family ... 4, 5, 83, 88, 103, 406, 407
\m@th ..... 188
tex commands:
\tex_fam:D ..... 162, 164, 166
\tex_hskip:D ..... 277, 284
\tex_mskip:D ..... 276, 283
\textrm ..... 11, 160
\textfractionsolidus ..... 4, 102
tl commands:
\tl_new:N ..... 61, 62, 63, 64, 65

U
use commands:
\use:n ..... 115
\UseInstance ..... 398, 399, 404, 407, 408

V
\vphantom ..... 190, 266, 312

X
xfrac internal commands:
\l_xfrac_cm_std_bool ..... 25, 363
\l_xfrac_denominator_bot_sep_dim ..... 51, 109, 287, 296
\l_xfrac_denominator_font_change: ..... 66, 68, 161, 170, 310
\l_xfrac_denominator_font_tl ..... 61, 110, 162, 172
\l_xfrac_denominator_format:n ..... 66, 69, 111, 302
\l_xfrac_fontscales: ..... 66, 66, 138, 140, 255, 301
\l_xfrac_hscale_fp . 58, 112, 259, 305
\l_xfrac_math:n ..... 66, 67, 115, 116, 190, 193, 197, 262, 273, 280, 308
\l_xfrac_numerator_bot_sep_dim . .... 51, 120, 222, 227, 233
\l_xfrac_numerator_font_change: . .... 66, 70, 163, 175, 264
\l_xfrac_numerator_font_tl ..... 61, 118, 164, 177
\l_xfrac_numerator_format:n ..... 66, 71, 119, 256
\l_xfrac_numerator_top_sep_dim . .... 51, 121, 219, 242
\l_xfrac_phantom_tl 61, 122, 266, 312
\l_xfrac_relscale: 66, 72, 127, 133, 143
\l_xfrac_scale_factor_fp 58, 123, 143
\l_xfrac_slash_box ..... 48, 134, 191, 212, 213, 241, 279, 290
\l_xfrac_slash_left_muskip ..... 56, 149, 283
\l_xfrac_slash_left_sep_dim ..... 51, 148, 284
\l_xfrac_slash_right_muskip ..... 56, 151, 276
\l_xfrac_slash_right_sep_dim ..... 51, 150, 277
\l_xfrac_slash_symbol_font_change: ..... 66, 73, 165, 180, 199
\l_xfrac_slash_symbol_font_tl .. ..... 61, 153, 166, 182
\l_xfrac_slash_symbol_format:n .. ..... 66, 74, 154, 195
\l_xfrac_slash_symbol_tl 61, 152, 201
\l_xfrac_text_or_math:n ..... 66, 75, 160, 169, 186
\l_xfrac_tmp:w ..... 50, 206, 224, 235, 253, 289, 293, 299
\l_xfrac_tmp_box ..... 48, 130, 189
\l_xfrac_vscales_fp . 58, 155, 260, 306

```