

1. Grammar symbols: Used cross reference.

Reference of each grammar's symbol used within each rule's productions. The index uses the triple: rule name, its subrule no, and the symbol's position within the symbol string.

2. # *::.**

R3asterics 1.2

3. # parallel-la-boundary::.

Rpp_la_bndary 1.2

4. # parallel-thread-function::.

Rpp_thread_fnct 1.2

5. (::

Ropen_par 2.1

6.)::

Rclose_par 2.1

7. NS_identifier::TH_identifier::.

Rpp_thread_fnct 1.3 Rpp_thread_fnct_id 1.3 Rpp_la_bndary 1.3

8. NS_la_expr_src::TH_la_expr_src::.

Rpp_la_bndary_stc 1.3

9. NS_lint_balls::TH_lint_balls::.

Rlint 1.3

10. NS_o2_code_end::TH_o2_code_end::.

R3asterics 1.3

11. NULL thread::.

Rpp_thread_fnct 2.3 Rpp_thread_fnct_id 2.3 Rpp_la_bndary 2.3 Rpp_la_bndary_stc 2.3

12. R3asterics::.

Rpp_thread_fnct_phrase 1.5

13. Rclose_par::.

Rparallel_parser_phrase 1.5

14. Rlint::

Rparallel_parser_phrase 1.1 Rparallel_parser_phrase 1.3 Rparallel_parser_phrase 1.6 Rpp_thread_fnct_phrase 1.2 Rpp_thread_fnct_phrase 1.4 Rpp_thread_fnct_phrase 1.6 Rpp_la_bndary_phrase 1.2 Rpp_la_bndary_phrase 1.4

15. Ropen_par::

Rparallel_parser_phrase 1.2

16. Rparameters::

Rparallel_parser_phrase 1.4

17. Rpp_la_bndary::

Rpp_la_bndary_phrase 1.1

18. Rpp_la_bndary_phrase::

Rparameters 1.2

19. Rpp_la_bndary_stc::

Rpp_la_bndary_phrase 1.3

20. Rpp_thread_fnct::

Rpp_thread_fnct_phrase 1.1

21. Rpp_thread_fnct_id::

Rpp_thread_fnct_phrase 1.3

22. Rpp_thread_fnct_phrase::

Rparameters 1.1

23. ϵ ::

Rlint 2.1

24. identifier::

Rpp_thread_fnct_id 1.2

25. la-express-source::

Rpp_la_bndary_stc 1.2

26. lint::

Rlint 1.2

27. |?|::

Ropen_par 1.1 Rclose_par 1.1 Rpp_thread_fnct 2.2 Rpp_thread_fnct 3.1 Rpp_thread_fnct_id 2.2
Rpp_thread_fnct_id 3.1 R3asterics 2.1 Rpp_la_bndary 2.2 Rpp_la_bndary 3.1 Rpp_la_bndary_stc 2.2
Rpp_la_bndary_stc 3.1

28. |||::

Rlint 1.1 Rpp_thread_fnct 1.1 Rpp_thread_fnct 2.1 Rpp_thread_fnct_id 1.1 Rpp_thread_fnct_id 2.1
R3asterics 1.1 Rpp_la_bndary 1.1 Rpp_la_bndary 2.1 Rpp_la_bndary_stc 1.1 Rpp_la_bndary_stc 2.1

29. Grammar Rules's First Sets.**30. *Rparallel_parser_phrase* # in set: 3.**

(|?| |||

31. *Rlint^ε* # in set: 1.

|||

32. *Ropen_par* # in set: 2.

(|?|

33. *Rclose_par* # in set: 2.

) |?|

34. *Rparameters* # in set: 2.

|?| |||

35. *Rpp_thread_fnct_phrase* # in set: 2.

|?| |||

36. *Rpp_thread_fnct* # in set: 2.

|?| |||

37. *Rpp_thread_fnct_id* # in set: 2.

|?| |||

38. *R3asterics* # in set: 2.

|?| |||

39. *Rpp_la_bndary_phrase* # in set: 2.

|?| |||

40. *Rpp_la_bndary* # in set: 2.

|?| |||

41. *Rpp_la_bndary_stc* # in set: 2.

|?| |||

42. LR State Network.

List of productions with their derived LR state lists. Their subrule number and symbol string indicates the specific production being derived. The “▷” symbol indicates the production’s list of derived states from its closed state. Multiple lists within a production indicate 1 of 2 things:

- 1) derived string that could not be merged due to a lr(1) conflict
- 2) partially derived string merged into another derived lr states

A partially derived string is indicated by the “merged into” symbol [↗] used as a superscript along with the merged into state number.

43. Rparallel_parser_phrase.

1 Rlint Ropen_par Rlint Rparameters Rclose_par Rlint
 ▷ 1 4 5 6 7 10 11

44. Rlint.

```

1 ||| lint NS_lint_balls::TH_lint_balls
  ▷ 1 2 3
  ▷ 5↗2
  ▷ 10↗2
  ▷ 24↗2
  ▷ 30↗2
  ▷ 32↗2
  ▷ 34↗2
  ▷ 39↗2
2 ε
  ▷ 1
  ▷ 5
  ▷ 10
  ▷ 24
  ▷ 30
  ▷ 32
  ▷ 34
  ▷ 39

```

45. Ropen_par.

```

1 |?|
  ▷ 4 12
2 (
  ▷ 4 13

```

46. Rclose_par.

```

1 |?|
  ▷ 7 8
2 )
  ▷ 7 9

```

47. Rparameters.

```

1 Rpp_thread_fnct_phrase Rpp_la_bndary_phrase
  ▷ 6 18 23

```

48. Rpp_thread_fnct_phrase.

```

1 Rpp_thread_fnct Rlint Rpp_thread_fnct_id Rlint R3asterics Rlint
  ▷ 6 32 33 34 35 39 40

```

49. Rpp_thread_fnct.

```

1 ||| # parallel-thread-function NS_identifier::TH_identifier
  ▷ 6 15 17
2 ||| |?| NULL
  ▷ 6 15 16
3 |?|
  ▷ 6 14

```

50. Rpp_thread_fnct_id.

```

1 ||| identifier NS_identifier::TH_identifier
  ▷ 33 42 44
2 ||| |?| NULL
  ▷ 33 42 43
3 |?|
  ▷ 33 41

```

51. R3asterics.

```

1 ||| # *** NS_o2_code_end::TH_o2_code_end
  ▷ 35 37 38
2 |?|
  ▷ 35 36

```

52. Rpp_la_bndary_phrase.

```

1 Rpp_la_bndary Rlint Rpp_la_bndary_stc Rlint
  ▷ 18 24 25 30 31

```

53. Rpp_la_bndary.

```

1 ||| # parallel-la-boundary NS_identifier::TH_identifier
  ▷ 18 20 22
2 ||| |?| NULL
  ▷ 18 20 21
3 |?|
  ▷ 18 19

```

54. Rpp_la_bndary_stc.

```

1 ||| la-express-source NS_la_expr_src::TH_la_expr_src
  ▷ 25 27 29
2 ||| |?| NULL
  ▷ 25 27 28
3 |?|
  ▷ 25 26

```

55. List of reducing states.

The following legend indicates the type of reducing state.
Points 2–4 are states that must meet the lr(1) condition:

- 1) r — only 1 production reducing
- 2) r^2 — 2 or more reducing productions
- 3) s/r — shift and 1 reducing production
- 4) s/r^2 — shift and multiple reducing productions

$\subset 1^{s/r} \quad 3^r \quad 5^{s/r} \quad 8^r \quad 9^r \quad 10^{s/r} \quad 11^r \quad 12^r \quad 13^r \quad 14^r \quad 16^r \quad 17^r \quad 19^r \quad 21^r \quad 22^r \quad 23^r \quad 24^{s/r} \quad 26^r$
 $28^r \quad 29^r \quad 30^{s/r} \quad 31^r \quad 32^{s/r} \quad 34^{s/r} \quad 36^r \quad 38^r \quad 39^{s/r} \quad 40^r \quad 41^r \quad 43^r \quad 44^r$

56. Lr1 State's Follow sets and reducing lookahead sets.

Notes on Follow set expressions:

1) The “follow set” for rule uses its literal name and tags its grammar rule rank number as a superscript. Due to space limitations, part of the follow set information uses the rule’s literal name while the follow set expressions refers to the rule’s rank number. This $\langle \text{rule name}, \text{rule rank number} \rangle$ tuple allows you the reader to decipher the expressions. Transitions are represented by $S_x R_z$ whereby S is the LR1 state identified by its “x” subscript where other transient calculations occur within the LR1 state network. R indicates the follow set rule with the subscript “z” as its grammar rank number that contributes to the follow set.

The \nearrow^x symbol indicates that a merge into state “x” has taken place. That is, the reduced subrule that depends on this follow set finds its follow set in 2 places: its birthing state that generated the sequence up to the merged into state, and the birthing state that generated the “merged into” state. So the rule’s “follow set” calculation must also continue its calculation within the birth state generating the “x merged into” state.

State: 1 Follow Set contributors, merges, and transitions

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{parallel_parser_phrase}}^1$

Local follow set yield:

eolr.

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{lint}}^2 \quad R_{1.1.1} \nearrow^{34} \nearrow^{32} \nearrow^{24} \nearrow^{39} \nearrow^{30} \nearrow^5 \nearrow^{10}$

Local follow set yield:

|?|, (.

State: 4 Follow Set contributors, merges, and transitions

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{open_par}}^3 \quad R_{1.1.2} \quad R_{1.1.3}$

Local follow set yield:

|?|, |||.

State: 5 Follow Set contributors, merges, and transitions

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{lint}}^2 \quad R_{1.1.3}$

Local follow set yield:

|?|, |||.

State: 6 Follow Set contributors, merges, and transitions

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{parameters}}^5 \quad R_{1.1.4}$

Local follow set yield:

|?|,).

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{pp_thread_fnct_phrase}}^6 \quad R_{5.1.1}$

Local follow set yield:

|?|, |||.

$\leftarrow \text{Follow set Rule} \rightarrow \leftarrow \text{follow set symbols contributors} \rightarrow$
 $R_{\text{pp_thread_fnct}}^7 \quad R_{6.1.1} \quad R_{6.1.2}$

Local follow set yield:

|?|, |||.

State: 7 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rclose_par⁴ R_{1..1..5} R_{1..1..6} S₁R₁

Local follow set yield:

|||.

State: 10 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rlint² R_{1..1..6} S₁R₁

Local follow set yield:

State: 18 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rpp_la_bndary_phrase¹⁰ R_{5..1..2} S₆R₅

Local follow set yield:

\leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow
Rpp_la_bndary¹¹ R_{10..1..1} R_{10..1..2}

Local follow set yield:

|?|, |||.

State: 24 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rlint² R_{10..1..2}

Local follow set yield:

|?|, |||.

State: 25 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rpp_la_bndary_stc¹² R_{10..1..3} R_{10..1..4} S₁₈R₁₀

Local follow set yield:

|||.

State: 30 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rlint² R_{10..1..4} S₁₈R₁₀

Local follow set yield:

|?|, |||.

State: 32 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rlint² R_{6..1..2}

Local follow set yield:

|?|, |||.

State: 33 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule $\rightarrow \leftarrow$ follow set symbols contributors \rightarrow

Rpp_thread_fnct_id⁸ R_{6..1..3} R_{6..1..4}

Local follow set yield:

|?|, |||.

State: 35 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule \rightarrow follow set symbols contributors \rightarrow
 R3asterics⁹ R_{6.1.5} R_{6.1.6} S₆R₆
 Local follow set yield:
 |||.

State: 39 Follow Set contributors, merges, and transitions
 \leftarrow Follow set Rule \rightarrow follow set symbols contributors \rightarrow
 R_{lint²} R_{6.1.6} S₆R₆
 Local follow set yield:

57. Common Follow sets.

58. LA set: 1.

eolr.

59. LA set: 2.

$|?|, |r|.$

60. LA set: 3.

$|?|,).$

61. LA set: 4.

$|?|, |r|,).$

62. Index.

R₁ --- Rparallel_parser_phrase: 43.
R₁₀ --- Rpp_la_bndary_phrase: 52.
R₁₁ --- Rpp_la_bndary: 53.
R₁₂ --- Rpp_la_bndary_stc: 54.
R₂ --- Rlint: 44.
R₃ --- Ropen_par: 45.
R₄ --- Rclose_par: 46.
R₅ --- Rparameters: 47.
R₆ --- Rpp_thread_fnct_phrase: 48.
R₇ --- Rpp_thread_fnct: 49.
R₈ --- Rpp_thread_fnct_id: 50.
R₉ --- R3asterics: 51.
Rclose_par: 33.
Rlint: 31.
Ropen_par: 32.
Rparallel_parser_phrase: 30.
Rparameters: 34.
Rpp_la_bndary: 40.
Rpp_la_bndary_phrase: 39.
Rpp_la_bndary_stc: 41.
Rpp_thread_fnct: 36.
Rpp_thread_fnct_id: 37.
Rpp_thread_fnct_phrase: 35.
R3asterics: 38.

parallel_parser_ph_th_idx.w

Date: January 14, 2015 at 15:40

File: parallel_parser_ph_th_idx.w

	Section	Page
Grammar symbols: Used cross reference	1	1
# ***:	2	1
# parallel-la-boundary:	3	1
# parallel-thread-function:	4	1
(:	5	1
):	6	1
NS_identifier:TH_identifier:	7	1
NS_la_expr_src::TH_la_expr_src:	8	1
NS_lint_balls::TH_lint_balls:	9	1
NS_o2_code_end::TH_o2_code_end:	10	1
NULL thread:	11	1
R3asterics:	12	1
Rclose_par:	13	1
Rlint:	14	2
Ropen_par:	15	2
Rparameters:	16	2
Rpp_la_bndary:	17	2
Rpp_la_bndary_phrase:	18	2
Rpp_la_bndary_stc:	19	2
Rpp_thread_fnct:	20	2
Rpp_thread_fnct_id:	21	2
Rpp_thread_fnct_phrase:	22	2
ϵ :	23	2
identifier:	24	2
la-express-source:	25	2
lint:	26	2
? :	27	3
:	28	3

Grammar Rules's First Sets	29	4
<i>Rparallel_parser_phrase</i> # in set: 3	30	4
<i>Rlint^ε</i> # in set: 1	31	4
<i>Ropen_par</i> # in set: 2	32	4
<i>Rclose_par</i> # in set: 2	33	4
<i>Rparameters</i> # in set: 2	34	4
<i>Rpp_thread_fnct_phrase</i> # in set: 2	35	4
<i>Rpp_thread_fnct</i> # in set: 2	36	4
<i>Rpp_thread_fnct_id</i> # in set: 2	37	4
<i>R3asterics</i> # in set: 2	38	4
<i>Rpp_la_bndary_phrase</i> # in set: 2	39	4
<i>Rpp_la_bndary</i> # in set: 2	40	4
<i>Rpp_la_bndary_stc</i> # in set: 2	41	4
LR State Network	42	4
<i>Rparallel_parser_phrase</i>	43	4
<i>Rlint</i>	44	5
<i>Ropen_par</i>	45	5
<i>Rclose_par</i>	46	5
<i>Rparameters</i>	47	5
<i>Rpp_thread_fnct_phrase</i>	48	5
<i>Rpp_thread_fnct</i>	49	6
<i>Rpp_thread_fnct_id</i>	50	6
<i>R3asterics</i>	51	6
<i>Rpp_la_bndary_phrase</i>	52	6
<i>Rpp_la_bndary</i>	53	6
<i>Rpp_la_bndary_stc</i>	54	6
List of reducing states	55	7
Lr1 State's Follow sets and reducing lookahead sets	56	8
Common Follow sets	57	11
LA set: 1	58	11
LA set: 2	59	11
LA set: 3	60	11
LA set: 4	61	11
Index	62	12